


# State of Alaska Department of Community and Economic Development Rural Energy Group

813 West Northern Lights Blvd. Anchorage, Alaska 99503




# **NUNAPITCHUK, ALASKA**

BULK FUEL UPGRADES
ISSUED FOR BIDDING
JULY 2021



# PROJECT AREA MAP







## SHFFT INDEX

HEET NUM	SHEET TITLE
GENERAL	
G1	COVER
G2	GENERAL NOTES, LEGEND, AND ABBREVIATIONS
G3	SURVEY CONTROL
G4	COMPONENTS SCHEDULE
G5	SETBACK AND SIGNAGE PLAN
CIVIL	WOINITY MAD
C1	VICINITY MAP
C2 C3	OPERATING SCHEMATIC
C4	SITE PLAN PIPING PLAN
C5	PILE LAYOUT PLAN
C6	TYPICAL SECTION
C7	TYPICAL SECTION
C8	TYPICAL SECTION
C9	30,000 GAL DOUBLE WALL TANK
C10	5,000 GAL DOUBLE WALL PROTECTED DISPENSING TANK
C10	MISCELLANEOUS TANK DETAILS
C12	HOSE REEL DISPENSER
C13	THERMOPROBE AND PILE DETAILS
C14	MISCELLANEOUS DETAILS
C15	CONNEX UPGRADES
C16	FENCE DETAILS
C17	FENCE DETAILS
STRUCTURAL	1 2/102 32 // 1120
S1	GENERAL STRUCTURAL NOTES
S2	STRUCTURAL STEEL LAYOUT
S3	BEAM CONNECTION DETAILS
S4	BEAM CONNECTION DETAILS
S5	BEAM CONNECTION DETAILS
ELECTRICAL	
E1	NOTES, LEGEND, & ABBREVIATIONS
E2	ONE-LINE DIAGRAM AND PANEL SCHEDULE
E3	CONDUIT DEVELOPMENT PLAN
E4	CONDUIT SCHEDULE
E5	ELECTRICAL SITE PLAN, GROUNDING, & LIGHTING PLAN
E6	POWER & CONTROLS PLAN (1 OF 2)
E7	POWER & CONTROLS PLAN (2 OF 2)
E8	CLASSIFICATION PLAN
E9	GROUNDING AND ELECTRICAL DETAILS
E10	PANEL LAYOUT
E11	WIRE LIST AND COMPONENT SCHEDULE
E12	CONTROL POWER LADDER DIAGRAM
E13	GASOLINE STORAGE TANK FLOAT LADDER DIAGRAMS
E14	TRANSFER PUMPS P-1 AND P-2 LADDER DIAGRAMS
E15	TRANSFER PUMPS P-3 AND P-4 LADDER DIAGRAMS
E16	GASOLINE DISPENSER PUMP LADDER DIAGRAM
E17	DIESEL STORAGE TANK FLOAT LADDER DIAGRAMS
E18	TRANSFER PUMPS P-5 AND P-6 LADDER DIAGRAMS
E19	TRANSFER PUMPS P-7 AND P-8 LADDER DIAGRAMS

DIESEL DISPENSER PUMP LADDER DIAGRAM

### PROJECT SCOPE

THIS PROJECT PROVIDES FOR THE CONSTRUCTION OF A NEW BULK FUEL STORAGE AND HANDLING FACILITY IN NUNAPITCHUK, ALASKA. SPECIFIC ACTIVITIES WILL INCLUDE THE FOLL DIMINIS.

- A NEW BULK FUEL TANK FARM WITH NINE HORIZONTAL, SKID MOUNTED ABOVEGROUND STORAGE TANKS MOUNTED TO PILE FOUNDATIONS.
- FUEL TANKS INCLUDE:
  - (4) NEW 30,000-GALLON DOUBLE WALL GASOLINE BULK STORAGE TANKS
  - (4) NEW 30,000-GALLON DOUBLE WALL DIESEL BULK STORAGE TANKS
  - (1) NEW 5,000-GALLON DUAL PRODUCT, PROTECTED, DISPENSING TANK
- NEW TWO PRODUCT BARGE FILL HEADER
- NEW ELEVATED BOARDWALKS INCLUDE:
  - 1. EXTENSION FROM EXISTING BOARDWALK NORTH OF THE PROPOSED SITE
  - 2. 40'x50' FUELING AND TURNAROUND AREA
  - 3. CATWALK TO BULK FUEL TANK ACCESS LADDERS
  - 4. WALKWAY TO RIVER FUELING AREA
- NEW DUAL PRODUCT HOSE REEL DISPENSERS WITH MECHANICAL METERS
- POWER SERVICE, LIGHTING, AND ELECTRICAL CONTROLS AS REQUIRED

  PROMPTS OF THE CONTROL OF THE PROPERTY OF T
- REQUIRED SPILL CONTINGENCY EQUIPMENT HOUSED IN AN 8'x20' PILE SUPPORTED CONNEX
- RETAIL ATTENDANT KIOSK HOUSED IN AN 8'x20' PILE SUPPORTED CONNEX CONTRACTOR PROVIDED PRE-ENGINEERED DOCK & GANGWAY.

### GENERAL NOTES

- THE CONTRACTOR SHALL PROTECT ALL ITEMS NOT SCHEDULED FOR DEMOLITION DURING CONSTRUCTION. DISTURBED AREAS SHALL BE RESTORED TO PRE-CONSTRUCTION CONDITION.
- 2. ALL EXISTING UTILITIES MAY NOT BE SHOWN ON THESE PLANS. THE CONTRACTOR SHALL CONSULT WITH THE APPROPRIATE UTILITY ORGANIZATIONS TO VERIFY AND LOCATE UTILITIES PRIOR TO CONSTRUCTION. SEE UTILITY CONTACT INFORMATION ON THIS SHEET.
- 3. THE CONTRACTOR MUST COMPLY WITH APPLICABLE FEDERAL AND STATE OSHA
  REGULATIONS. THE CONTRACTOR SHALL MAINTAIN ALL SIGNS, BARRICADES, WARNING LIGHTS
  AND OTHER PROTECTIVE DEVICES NECESSARY FOR SAFETY AND TRAFFIC CONTROL.
- 4. THE CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATING HIS WORK WITH EXISTING FACILITY OPERATORS, OTHER CONTRACTORS, SUBCONTRACTORS, THE CITY AND STATE AND FEDERAL AUTHORITIES.
- 5. THE DRAWINGS ARE DIAGRAMMATIC AND DO NOT NECESSARILY SHOW ALL FEATURES OF THE REQUIRED WORK. PROVIDE ALL LABOR, EQUIPMENT AND MATERIALS REQUIRED FOR A COMPLETE, AND CODE COMPLIANT SYSTEM. VERIFY EXISTING FIELD CONDITIONS PRIOR TO STARTING CONSTRUCTION. IMMEDIATELY CONTACT THE ENGINEER FOR CLARIFICATION OF QUESTIONABLE ITEMS OR APPARENT CONFLICTS.
- 5. THE CONTRACTOR SHALL PREPARE AND SUBMIT A SWPPP IF ONE IS REQUIRED.
- 6. CONTRACTOR SHALL PROCURE AND ATTACH TANK NUMBERING LABELS.
- 7. ALL ITEMS TO BE INSTALLED ARE NEW UNLESS SPECIFICALLY INDICATED AS EXISTING. INSTALL ALL MATERIALS AND EQUIPMENT IAW MANUFACTURERS RECOMMENDATIONS, INSTRUCTIONS, AND INSTALLATION DRAWINGS, UNLESS OTHERWISE INDICATED ON THE DRAWINGS.
- 8. THE SPECIFICATION OF A NAME BRAND PRODUCT FOLLOWED BY THE "OR EQUAL" PHRASE IS DONE MERELY TO ESTABLISH THE MINIMUM LEVEL OF QUALITY OF MATERIALS AND EQUIPMENT REQUIRED AND IS NOT A PRODUCT ENDORSEMENT. SUBMIT ANY PROPOSED SUBSTITUTIONS FOR REVIEW AND APPROVAL, UNLESS "NO SUBSTITUTIONS" IS SPECIFIED.
- FACILITY DESIGN IS IN ACCORDANCE WITH THE 2012 INTERNATIONAL FIRE CODE, STATE OF ALASKA FIRE AND SAFETY REGULATIONS ADMINISTRATIVE CODES 13 AAC 50, 13 AAC 55, AND THE MOST RECENT MEMORANDUM OF AGREEMENT BETWEEN THE AEA AND THE STATE OF ALASKA FIRE MARSHALL
- 10. CONTRACTOR TO PROVIDE SIGNAGE IAW THE SIGN SCHEDULE, AND AS IDENTIFIED ELSEWHERE IN THE DRAWINGS.
  - 11. PERFORM WORK WITH SKILLED CRAFTSMEN SPECIALIZED IN SAID WORK. INSTALL ALL MATERIALS IN A NEAT, ORDERLY, AND SECURE FASHION, AS REQUIRED BY THE DRAWINGS AND SPECIFICATIONS AND COMMONLY RECOGNIZED STANDARDS OF GOOD WORKMANSHIP.
- 12. PIPE SUPPORTS SHALL BE SPACED A MAXIMUM OF 10' ON CENTER IAW THE UPC.
- CONTRACTOR SHALL MAINTAIN A "REDLINE" SET OF DRAWINGS TO REFLECT FIELD CHANGES
  THROUGHOUT CONSTRUCTION. RED LINE CONSTRUCTION DRAWINGS SHALL BE SUBMITTED
  TO ENGINEER AT COMPLETION OF THE PROJECT.
- 14. ALL WORK SHALL BE PERFORMED IN ACCORDANCE WITH U.S. ENVIRONMENTAL PROTECTION AGENCY, ALASKA DEPARTMENT OF ENVIRONMENTAL CONSERVATION, AND STATE AND FEDERAL OCCUPATIONAL HEALTH AND SAFETY REGULATIONS.

CALL BEFORE YOU DIG				
WATER/SEWER	CITY OF NUNAPITCHUK 907-527-5327			
ELECTRIC	AVEC 907-561-1818			

### ABBREVIATIONS

ADEC	ALASKA DEPARTMENT OF ENVIRONMENTAL	LB	POUND
	CONSERVATION		
ADOT	ALASKA DEPARTMENT OF TRANSPORTATION	M	METERS
AEA	ALASKA ENERGY AUTHORITY	MAX	MAXIMUM
ALCAP	ALUMINUM SURVEY CAP	MIL	0.001 INCH
ANSI	AMERICAN NATIONAL STANDARDS INSTITUTE	MIN	MINIMUM
API	AMERICAN PETROLEUM INSTITUTE	MNPT	MALE NATIONAL PIPE THREAD
APPROX	APPROXIMATE	MV	MOTORIZED BALL VALVE
ASTM	AMERICAN SOCIETY FOR TESTING OF MATERIALS		
AST	ABOVEGROUND STORAGE TANK	N	NORTH
ASV	ANTI-SIPHON VALVE	NC	NORMALLY CLOSED
AWS	AMERICAN WELDING SOCIETY	NFS	NON-FROST SUSCEPTIBLE SOIL
		NL	NUNAPITCHUK LIMITED
BLDG	BUILDING	NO	NORMALLY OPEN
BV	BALL VALVE	NPT	NATIONAL PIPE TAPERED THREAD
		NTS	NOT TO SCALE
CMP	CORRUGATED METAL PIPE	NWR	NATIONAL WILDLIFE REFUGE
CP	CONTROL PANEL		
CV	CHECK VALVE	OAE	OR APPROVED EQUAL
		OD	OUTSIDE DIAMETER
DEMO	DEMOLISH	OSHA	OCCUPATIONAL SAFETY AND HEALTH
DFT	DRY FILM THICKNESS		ADMINISTRATION
DIA	DIAMETER	OZ	OUNCE
DWG	DRAWING		
		PCC	PORTLAND CEMENT CONCRETE
E	EAST	PL	PLATE
EA	EACH	PT	PRESSURIZED TEST TAP
EL	ELEVATION	PRV	PRESSURE RELIEF VALVE
ELEC	ELECTRIC	PSF	POUNDS PER SQUARE FOOT
EPA	U.S. ENVIRONMENTAL PROTECTION AGENCY	PSI	POUNDS PER SQUARE INCH
ENGINEER	CRW ENGINEERING GROUP, LLC		
E-VENT	EMERGENCY VENT	R	RADIUS
		RF	RAISED FACE
*F	FAHRENHEIT		
FC	FLEX CONNECT	S	SEWER
FF	FINISH FLOOR ELEV.	SCH	SCHEDULE
FG.	FINISH GRADE	SHP0	STATE HISTORIC PRESERVATION OFFICE
FLV	FILL LIMITING VALVE	SIM	SIMILAR
FOR	FUEL OIL RETURN	SPEC	SPECIFICATION
FOS	FUEL OIL SUPPLY	SQ	SQUARE
FPT	FEMALE NATIONAL PIPE TAPERED THREAD	SS	STAINLESS STEEL
FT	FOOT OR FEET	SSPC	STEEL STRUCTURES PAINTING COUNCIL
04	ONIOE	STA	STATION
GA	GALLON	SY	SQUARE YARD
GAL	GALLON	TDU	TEMPODADY DENOU MADI
GALV	GALVANIZED GALLONS PER MINUTE	TBM	TEMPORARY BENCH MARK
GP <b>M</b>	GALLONS PER MINUTE	TS TYP	TUBE STEEL TYPICAL
HDPE	LIIOU DENCITY DOLVETUVLENE	IIP	TTPICAL
	HIGH DENSITY POLYETHYLENE HORSE POWER	UG	LINDEDODOLIND
HP HR	HOUR	UL	UNDERGROUND UNDERWRITERS LABORATORY
ПП	HOOK	UPC	UNIFORM PLUMING CODE
IAW	IN ACCORDANCE WITH	UST	UNDERGROUND STORAGE TANK
IBC	IN ACCORDANCE WITH INTERNATIONAL BUILDING CODE	ULSD	ULTRA LOW SULFUR DIESEL
ID IBC	INSIDE DIAMETER	OLOD	OLINA LOW SULFUR DIESEL
IFC	INSIDE DIAMETER INTERNATIONAL FIRE CODE	/	MITH
IPC	INTERNATIONAL PIRE CODE INTERNATIONAL PLUMBING CODE	w/ W	WITH
IFC	INTENNATIONAL FLUMDING CODE	W	WATER
LF	LINEAR FEET		
LI	LINEAR LEET		

### TESTING. STARTUP AND COMMISSIONING PROCEDURES


- CONTRACTOR SHALL PERFORM SYSTEM TESTING, STARTUP AND COMMISSIONING IN ACCORDANCE WITH THE PROCEDURES
  LISTED HERE AND IN ACCORDANCE WITH MANUFACTURER INSTRUCTIONS. LEAVE ALL WORK SITES IN AN ORDERLY CONDITION
  CONSISTENT WITH THAT FOUND UPON ARRIVAL.
- PRESSURE TEST ALL PIPING AND FILL OUT AEA-APPROVED PIPELINE PRESSURE TEST REPORTS, NOTIFY ENGINEER SEVEN DAYS PRIOR TO PLANNED PRESSURE TESTING. THE ENGINEER OR HIS APPROVED REPRESENTATIVE SHALL BE PRESENT DURING ALL PRESSURE TESTING UNLESS DIRECTED OTHERWISE IN WRITING. DELIVER ORIGINAL REPORTS TO AEA AND A COPY TO THE ENGINEER.
- 3. TEST ALL PRESSURE RELIEF AND ANTI-SIPHON VALVES FOR PROPER OPERATION AT SPECIFIED PRESSURE
- 4. CONTRACTOR SHALL BE PRESENT DURING INITIAL FILLING OF TANKS. UPON FILLING OF TANKS VERIFY PRODUCT LEVEL WITH GAUGING STICK AND RECALIBRATE ALL TANK GAUGES. REMOVE AND CLEAN ALL STRAINERS AFTER INITIAL FILLING.
- 5. CHECK ALL PUMPS FOR PROPER ROTATION. PRIOR TO OPERATING CENTRIFUGAL PUMPS PRIME THE PUMP CAVITY WITH FUEL.

  DURING COLD WEATHER (BELOW 40 'F), PRIOR TO INITIAL START UP, WARM PUMP BODY IN ACCORDANCE WITH

  MANUFACTURES'S RECOMMENDATION.
- 6. CHECK ALL CONTROL AND ALARM FUNCTIONS. MANIPULATE TANK FLOAT SWITCHES TO SIMULATE LOW AND HIGH LEVEL CONDITIONS. SET TIMING RELAYS FOR 30 SECONDS AND VERIFY TIME-OUT FUNCTION. RE-SET TIMERS TO SPECIFIED VALUES AFTER TESTING. VERIFY LATCHING AND RESET FUNCTIONS, EMERGENCY STOP FUNCTION, AND OPERATION OF ALL SIGNAL LAMPS AND HORNS. OBSERVE OPERATION OF MOTOR ACTUATED VALVES. VERIFY THAT ONSITE POWER GENERATION SYSTEM & AREA LIGHTING FUNCTION PROPERLY.
- 7. TEST THE RETAIL DISPENSER, AND ALL RELATED COMPONENTS.
- 8. VERIFY ALL SIGNS, PLACARDS, AND VALVE TAGS ARE PROPERLY LOCATED. VERIFY PROPER PRODUCT COLOR CODE AND LABELING FOR ALL TANKS AND PIPING.
- 9. INSTALL PADLOCKS ON ALL VALVES AND FENCE GATES. KEY ALL LOCKS ALIKE. PROVIDE (2) SPARE LOCKS AND KEYS.
- 10. INSTRUCT LOCAL OPERATORS IN THE OPERATION AND MAINTENANCE OF ALL SYSTEMS. PLACE SPARE PARTS, INCINERATOR, AND SPILL RESPONSE SUPPLIES IN DESIGNATED LOCATION.

## CIVIL LEGEND (GENERAL)


NOTE: SOME DETAILS UTILIZE SYMBOLS NOT IN THIS GENERAL LEGEND. WHERE THIS OCCURS, SYMBOLS ARE DEFINED ON THE SHEET IN WHICH THEY ARE USED.



# UTILITY LINE/PIPELINE DESIGNATIONS

DIESEL OR GASOLINE — XX — ABOVEGROUND PIPELINE: PROPOSED

### DETAIL/SECTION REFERENCES









BULK FUEL UPGRADES GENERAL NOTES, LEGEND, AND ABBREVIATIONS

NO. REVISION BY DATE
1 ISSUED FOR BIDDING AH 7/28/21

Dote7/28/21
Designed \_\_\_
Drawn\_\_\_\_Approved\_\_\_

heet No.

G2

KUSKOKWIM RIVER 2015 COORDINATE SYSTEM PARAMETERS: LINEAR UNIT: US SURVEY FEET DATUM: NAD83 ELLIPSOID: GRS 80

PROJECTION: RECTIFIED HOTINE OBLIQUE MERCATOR, SINGLE POINT LATITUDE OF CENTER: 60°40'00" N LONGITUDE OF CENTER: 162°00'00" W

AZIMUTH: 50°00'00" FALSE NORTHING: -15,500,000.0 FALSE EASTING: -19,100,000.0 GRID SCALE FACTOR: 1.000002 (EXACT)

THIS LDP (LOW DISTORTION PROJECTION) WAS DEVELOPED IN 2015 BY THE STATE OF ALASKA DOT&PF CENTRAL REGION SURVEY SECTION. THIS LDP COVERS COMMUNITIES ON AND AROUND THE LOWER KUSKOKWIM RIVER FROM THE RIVERS MOUTH TO THE COMMUNITY OF CHUATHBALUK. BERING SEA COASTAL COMMUNITIES FROM CHEFORNAK TO KONGIGANAK ARE ALSO

BASIS OF COORDINATES
THE BASIS OF COORDINATES IS NUNAPITCHUKS SECONDARY AIRPORT CONTROL (SAC) 16A-C, PID #DR6568 (CRW CONTROL POINT 601), NGS NAD83 (2011) PUBLISHED COORDINATE:

LATITUDE: 60°54'10.50262" N LONGITUDE: 162°26'38.07280" W ELLIP HT: 14.683 (M) ORTHO: 4.58 (M) / 15.0 (FT)

CONTROL POINTS WERE ESTABLISHED BY RAPID STATIC AND RTK GPS AND BY AN NGS PUBLISHED SOLUTION FOR CONTROL POINT 601. ALL OTHER CONTROL AND TOPO POINT POSITIONS WERE COMPUTED/REFERENCE VALUES FROM 601.

### VERTICAL CONTROL STATEMENT

THE VERTICAL DATUM IS GEOID 12B FROM THE NGS DATA SHEET FOR SECONDARY AIRPORT CONTROL (SAC) 16A-C, CRW CONTROL POINT 601. REMAINDER OF THE CONTROL POINT ELEVATIONS WERE ESTABLISHED BY RTK GPS FROM 601. A DIFFERENTIAL LEVEL LOOP WAS RUN FROM A TEMPORARY CONTROL POSITION TO TBM 351, THE NUNAPITCHUK HIGH SCHOOL FINISH FLOOR ON ITS WEST ENTRANCE.

ARMY CORP OF ENGINEERS FLOOD INFORMATION FOR NUNAPITCHUK, STATES ITS BASIS OF FLOOD INFORMATION IS BASED ON THE FIRST FLOOR OF NUNAPITCHUK HIGH SCHOOL. THIS WAS BASED 1972 FLOOD THAT IS BELIEVED TO REPRESENT THE 100 YEAR/BASE FLOOD ELEVATION. AN ELEVATION OF 100.0' WAS THE ASSUMED ELEVATION ASSIGNED TO THE FIRST FLOOR OF THE HIGH SCHOOL. TO COMPUTE LOCAL FLOOD DATUM FROM ASSUMED ELEVATIONS TO GEOID12B ELEVATIONS, SUBTRACT (-) 84.5 FEET.


FIRST FLOOR OF HIGH SCHOOL: 100.0' = 15.80' GEOID12B RECOMMEND BUILDING HEIGHT: 92.8' = 8.6' GEOID12B


### <u>NOTES</u>

- 1. ALL COORDINATES AND DIMENSIONS SHOWN ARE IN U.S. SURVEY FEET.
- 2. A FIELD SURVEY WAS CONDUCTED IN FEBRUARY 2021.
- 3. THE DEVELOPMENT OF THIS SURVEY CONTROL SHEET IS FOR THE NEW PROPOSED NUNAPITCHUCK TANK FARM/FUEL DOCK SITE.
- THE SITE CONTROL SHOWN WAS ESTABLISHED DURING A FEBRUARY SURVEY WITH METHODOLOGY DESCRIBED IN THE HORIZONTAL AND VERTICAL STATEMENT.
- CONTROL POINTS ARE SUBJECT TO SEASONAL DISTURBANCE, VERIFY HORIZONTAL COORDINATES AND VERTICAL ELEVATIONS BEFORE USE IN CONSTRUCTION TO BASIS OF COORDINATES.

LEGEND CONTROL POINT # CRW ALUMINUM CAP TEMPORARY BENCH MARK NGS PACS & SACS MONUMENT

TYPICAL CRW CONTROL (SET 2" ALCAP ON 5/8"X30" REBAR)





PROPOSED TANK FARM SITE NUNAPITCHUK HIGH SCHOOL US SURVEY 4049 US SURVEY 8399

SCALE: GRAPHIC





UPGRADE BULK

F B

G3

BRASS CAP MONUMENT

ALUMINUM ROD

SURVEY CONTROL

		TANK FARM \	ALVE SCHEDULE		
VALVE ID	SIZE	LOCATION	END CONNECTION	COMMENT	ID TAG REQ'D
BALL VALVES (BV)					
BV-1A TO BV8A	2"	TANK T1-T8 ISSUE	FLANGED	Tank Issue Isolation — N.C.	Y
BV-1B TO BV-8B	3"	TANK T1-T8 FILL	FLANGED	Tank Fill Isolation — N.C.	Y
BV-10	3"	BARGE HEADER	FLANGED	Barge Header Isolation — N.C.	Y
BV-11	3"	BARGE HEADER	FLANGED	Barge Header Isolation — N.C.	Y
BV-12 & BV-13	1 1/2"	BASE OF DISPENSER	FLANGED	Dispenser Isolation — N.O.	Y
MOTORIZED VALVES	(MV)		<u> </u>		
MV-1	2"	TANK 9A FILL	FLANGED	Locate MV on top of tank	Y
MV-2	2"	TANK 9A ISSUE	FLANGED	Locate MV on top of tank	Y
MV-3	2"	TANK 9B ISSUE	FLANGED	Locate MV on top of tank	Y
MV-4	2"	TANK 9B FILL	FLANGED	Locate MV on top of tank	Y
CHECK VALVES (CV)			•		
CV-1	3"	BARGE HEADER	FLANGED	-	N
CV-2	3"	BARGE HEADER	FLANGED	-	N
CV-1A TO CV-8A	2"	TANK T1-T8 ISSUE	FLANGED	Locate on top of tank	N
CV-1B TO CV-8B	3"	TANK T1-T8 FILL	FLANGED	Locate on top of tank	N
CV-9A & CV-9B	2"	TANK T9 FILL	FLANGED	Locate on top of tank	N
PRESSURE RELIEF V	'ALVES (PRV)		•		
PRV-1	1"	TANK T1 — FILL	FLANGED	PRESSURE RELIEF SET AT 30 PSI	Y
PRV-2	1"	TANK T5 -FILL	FLANGED	PRESSURE RELIEF SET AT 30 PSI	Y
PRV-3	1"	TANK T9A	FLANGED	PRESSURE RELIEF SET AT 30 PSI	Y
PRV-4	1"	TANK T9A	FLANGED	PRESSURE RELIEF SET AT 30 PSI	Υ
PRV-5	1"	TANK T9B	FLANGED	PRESSURE RELIEF SET AT 30 PSI	Y
PRV-6	1"	TANK T9B	FLANGED	PRESSURE RELIEF SET AT 30 PSI	Υ
SHEAR VALVES (SV)			•		
SV-1	1 1/2"	BASE OF DISPENSER	THREADED		N
SV-2	1 1/2"	BASE OF DISPENSER	THREADED		N
ANTI SIPHON VALVE	S (ASV)				
ASV-1 TO ASV-8	2"	TANK T1-T8 PUMP DISCHARGE	-	Provide if not integral to pump	N
ASV-9A & ASV-9B	2"	TANK T9A & 9B PUMP DISCHARGE	-	Provide if not integral to pump	N
FLOW LIMITING VAL	VES (FLV)				
FV-1 TO FV-8	3"	TANK T1-T8	6" Threaded	Mechanical Flow Limiting Valve	Υ
FV-9A & FV-9B	2"	TANK T9A & T9B	4" Threaded	Mechanical Flow Limiting Valve	Υ

		TANK FARM MISCEL	LANESS COM ON		•
COMPONENT ID	SIZE	LOCATION	END CONNECTION	COMMENT	ID TAG REQ'D
FLEX CONNECT (FC)					
FC-1 TO FC-8	2"	TANKS T1 TO T8 - PUMP ISO	FLANGED	12" LENGTH	N
FC-9A & FC-9B	2"	TANKS 9A & 9B - PUMP ISO	FLANGED	12" LENGTH	N
FC-10 & FC-11	1 1/2"	HOSE REEL ISO	MPT x FLOAT FLANGE	AS REQUIRED FOR FITUP	N
STRAINERS (S)					
S-1	3"	BARGE HEADER	FLANGED	_	N
S-2	3"	BARGE HEADER	FLANGED	_	N
QUICK COUPLER (QC	;)		<u> </u>		
QC-1	3"	BARGE HEADER	-	<del>-</del>	N
QC-2	3"	BARGE HEADER	-	<del>-</del>	N
METER (M), FILTER (F	F), HOSE REEL	(HR) - PREFABRICATED UNIT	<u> </u>		
1		COMB. METER, FILTER, HOSE REEL	-	(see Design Documents)	N
2		COMB. METER, FILTER, HOSE REEL	-	(see Design Documents)	N
EVEL SWITCH (LS)			·		
LS-1 TO LS-8	_	TANK T1-T8	Per tank penn.	Three Position Level Switch	N
LS-9A & 9B	_	TANK T9A & T9B	Per tank penn.	Four Position Level Switch	N

	PUMP SCHEDULE					
PUMP ID	TYPE	PRODUCT	LOCATION	MOTOR (HP)	ELECTRICAL	
P-1 TO P-4	SUBMERSIBLE	GASOLINE	TANK T1	3/4	208/230 VAC, 1-PH	
P-5 TO P-8	SUBMERSIBLE	DIESEL	TANK T5	3/4	208/230 VAC, 1-PH	
P-9A & P-9B	SUBMERSIBLE	DIESEL & GASOLINE	TANK 9A & 9B	3/4	208/230 VAC, 1-PH	

	TANK SCHEDULE						
TANK NUMBER	CAPACITY (GALLONS)	TANK TYPE	PRODUCT	NOTES			
T1 TO T4	30,000	HORIZONTAL DOUBLE WALL	GASOLINE	Owner Provided			
T5 T0 T8	30,000	HORIZONTAL DOUBLE WALL	DIESEL	Owner Provided			
T9A	2,500	HORIZONTAL PROTECTED, DISPENSING	GASOLINE	Owner Provided			
Т9В	2,500	HORIZONTAL PROTECTED, DISPENSING	DIESEL	Owner Provided			







BULK FUEL UPGRADES
COMPONENTS SCHEDULE

NUNAPITCHUK, ALASKA

DATE	AH 7/28/21				
Β	ΑH				
). REVISION	ISSUED FOR BIDDING				
Ö	-				

G4

# **SETBACK/SEPARATION REQUIREMENTS:**

THE PROPOSED TANK FARMS WILL PERFORM TWO FUNCTIONS — BULK STORAGE FOR AVEC & COMMUNITY, AND FLEET DISPENSING FOR COMMUNITY. ALL TANKS ARE INSTALLED ABOVE GROUND. TO COMPLY WITH THE REQUIREMENTS OF THE 2012 INTERNATIONAL FIRE CODE, THE 2013 ALASKA ENERGY AUTHORITY/DIVISION OF FIRE PREVENTION MEMORANDUM OF AGREEMENT, AND STATE OF ALASKA REGULATIONS THE FOLLOWING MINIMUM CLEARANCES ARE

- 10' FROM THE DISPENSER TO ALL BUILDINGS AND PROPERTY LINES.
- 15' FROM 751-12,000 GAL BULK STORAGE TANKS TO THE NEAREST PROPERTY LINE WHICH IS OR CAN BE BUILT
- 40' FROM 12,001-30,000 GAL BULK STORAGE TANKS TO THE NEAREST PROPERTY LINE WHICH IS OR CAN BE BUILT
- 25' FROM THE BULK TRANSFER HOSE STAND TO THE NEAREST TANK, THE NEAREST IMPORTANT BUILDING, THE NEAREST PROPERTY LINE WHICH IS OR CAN BE BUILT UPON, COMBUSTIBLE MATERIALS, AND FIXED SOURCES OF
- 50' FROM THE DISPENSER TO ALL UNPROTECTED TANKS. (INCLUDES STATIONARY TANK TRUCKS)

### WARNING SIGNS & INFORMATION PLACARD SCHEDULE:

PROVIDE ALL SIGNS INDICATED IN THE SCHEDULE BELOW, QUANTITY & LOCATION AS INDICATED ON THE DRAWINGS. ALL SIGNS SHALL BE CONSTRUCTED FROM 0.08" ALUMINUM PLATE, AND SIZED IAW 2012 IFC. SIGN LETTERING IS SHOWN BELOW IN QUOTATIONS. PROVIDE 3/16" HOLES IN ALL FOUR CORNERS. PROVIDE NON-REFLECTIVE VINYL BACKGROUND, 3M 3650-10, WITH 3M SERIES 225 HIGH PERFORMANCE VINYL LETTERS, ONE SIDE ONLY, COLOR AS INDICATED. ATTACH TO FENCING WITH GALVANIZED HOG RINGS OR STAINLESS STEEL CABLE TIES. SIGNAGE PLACED DIRECTLY ON TANKS SHALL CONSIST OF HIGH QUALITY ADHESIVE BACK DECALS OR PAINTED STENCILS.

WARNING SIGNS - RED LETTERING ON WHITE BACKGROUND (3" HIGH X 1/2" STROKE LETTERS)

- "DANGER FLAMMABLE LIQUIDS"
- 2 "NO SMOKING NO OPEN FLAMES"
- "FLAMMABLE \_\_\_\_\_ GALLONS GASOLINE" OR "COMBUSTIBLE \_\_\_\_ GALLONS DIESEL", INSERT VOLUME IN GALLONS AS APPROPRIATE. "FLAMMABLE

INFORMATIONAL PLACARDS - BLACK LETTERING ON WHITE BACKGROUND (2" HIGH 1/2" STROKE

- "IMPORTANT PRIOR TO DISPENSING: 1. SHUT OFF MOTOR

  - DISCHARGE YOUR STATIC ELECTRICITY BEFORE FUELING BY TOUCHING A METAL
  - SURFACE AWAY FROM THE NOZZLE
    3. TO PREVENT STATIC CHARGE, DO NOT RE-ENTER YOUR VEHICLE WHILE GASOLINE IS
  - 4. IF A FIRE STARTS, DO NOT REMOVE NOZZLE BACK AWAY IMMEDIATELY"
  - "IT IS UNLAWFUL AND DANGEROUS TO DISPENSE FUEL INTO UNAPPROVED CONTAINERS"
- "NO FILLING OF PORTABLE CONTAINERS IN OR ON A MOTOR VEHICLE. PLACE CONTAINER ON GROUND BEFORE FILLING"
- "IN CASE OF FIRE SPILL OR RELEASE:

  - USE EMERGENCY SHUTOFF
    CONTACT NUNAPICHUK LTD. (907-527-5719) REPORT ACCIDENT TO ADEC"
- PROVIDE ADEC SPILL SIGN: CONTRACTOR TO CONTACT ADEC FOR CURRENT SPILL REPORTING PLACARD (907-269-3063)
- (9) "SPILL CONTINGENCY EQUIPMENT"
- (10) "EMERGENCY SHUTOFF" - SEE ELECTRICAL FOR SIGN LOCATIONS
- "PRESSURE NOT TO EXCEED 75 PSI" (NOTE THIS SIGN SHALL BE PERMANENTLY AFFIXED TO THE BARGE HEADER SUPPORT).


INSTRUCTION PLACARDS - BLUE LETTERING ON WHITE BACKGROUND (1/2" HIGH X 3/8" STROKE LETTERS)

- 12 DISPENSING INSTRUCTIONS:
  - DISPENSING IS TO BE CONDUCTED BY ATTENDANT SHUT OFF VEHICLE

  - RESET METER SET DESIRED VOLUME UNWIND HOSE AS REQUIRED, PLACE NOZZLE IN FUEL RECEPTACLE PRESS PUMP START BUTTON

  - DEPRESS NOZZLE LEVER TO BEGIN FLOW
  - WHEN FUELING IS COMPLETE, PRESS PUMP STOP BUTTON

  - HANG UP NOZZLE SEE ATTENDANT FOR PAYMENT AND RECEIPT
- (13) PROVIDE PLACARDS INDICATING PRODUCT TYPE AT HOSE REEL (TYP 2)








UPGRADES SIGNAGE BULK TBACK


H B

G5

TANK FARM SITE PLAN







### **GENERAL NOTES:**

- SYSTEM REPRESENTATIONS ON THIS SHEET ARE SCHEMATIC. SEE SITE PLAN, COMPONENT SCHEDULES, SPECIFICATIONS, AND TANK DETAILS FOR MORE SPECIFIC INFORMATION ON COMPONENT
- 2. NOT ALL PIPE FITTINGS (BENDS, REDUCERS, BUSHINGS, ETC.) ARE SHOWN. CONTRACTOR SHALL PROVIDE ALL NECESSARY FITTINGS FOR PROPER COMPONENT FIT-UP.
- 3. NOT ALL TANK APPURTENANCES (VENTS, ETC.) ARE SHOWN ON THIS SHEET. SEE TANK SHEETS FOR COMPONENT CALLOUTS AND INSTALLATION DETAILS.
- 4. SEE SHEET G2 FOR SYMBOL LEGEND.

### TANK FARM OPERATIONAL NARRATIVE

### FILLING TANK FARM FROM BARGE

THE TANK FARM WILL BE FILLED VIA A TWO PRODUCT BARGE HEADER WITH TWO 3-INCH FILL PIPELINES. BEFORE BEGINNING THE FILL PROCESS THE OPERATOR SHALL CONFIRM THAT ALL TANK ISOLATION VALVES ARE CLOSED. BULK TANKS SHOULD BE FILLED ONE AT A TIME BY SECUENTIALLY OPENING AND CLOSING INDIVIDUAL TANK ISOLATION BALL VALVES LINE PRESSURE WILL BE SUPPLIED BY THE BARGE PUMPING SYSTEM. THE TANK FARM OPERATOR WILL MONITOR THE FILLING PROCESS VIA CLOCK GAUGES AND/OR GAUGING ROD AT EACH TANK. WHEN THE TANK LEVEL REACHES 90%, A LIGHT ON THE CONTROL PANEL WILL INDICATE THAT THE TANK IS FULL. IF FILLING CONTINUES TO THE 95% LEVEL, THE TANKS MECHANICAL FILL LIMITER WILL STOP FLOW. ADDITIONALLY, A FLOAT AT THE 95% LEVEL WILL ACTIVATE AN ALARM AND THE "TANK OVERFULL" LIGHT WILL ILLUMINATE. AT THE CONCLUSION OF FILLING, CLOSE BARGE HEADER & TANK ISOLATION VALVES AND DISCONNECT FILL HOSE.

FILLING THE DISPENSING TANK
THE DUAL PRODUCT DISPENSING TANK CONTAINS TWO COMPARTMENTS, ONE FOR GASOLINE AND ONE FOR DIESEL. THE COMPARTMENTS ARE FILLED FROM CORRESPONDING BULK TANKS T1-T8. THE DISPENSING TANK FILL OPERATION IS CONTROLLED MANUALLY FROM CP-1 LOCATED WITHIN THE SALES KIOSK, FLOAT SWITCHES MONITOR THE LEVEL OF FUEL IN T9A AND T9B. WHEN FUEL LEVEL(S) FALL BELOW THE 50%-FULL POINT, LOW LEVEL LIGHTS WILL ILLUMINATE ON CP-1. SELECT A BULK TANK TO TRANSFER FROM, ENSURE THAT THE SELECTED BULK TANK HAS SUFFICIENT FUEL FOR THE TRANSFER. PRESS THE PUMP START BUTTON ON CP-1. HIGH LEVEL FLOAT SWITCHES WITHIN THE DISPENSING TANK AUTOMATICALLY DE-ENERGIZE THE TRANSFER PUMP AND CLOSE THE MOTORIZED BALL VALVE WHEN THE FUEL LEVEL REACHES 90% FULL. IF THE MOTORIZED VALVE & PUMP FAIL TO SHUTOFF, A MECHANICAL FILL LIMITER WILL STOP FUEL FLOW AT 95% AND AN ALARM WILL SOUND. DO NOT LEAVE THE FACILITY WHEN TRANSFERS ARE UNDERWAY!

### HOSE REEL DISPENSER OPERATION

PRIOR TO FILLING, TURN OFF ENGINE, CHOCK WHEELS AND CONNECT STATIC GROUNDING CABLE. OPEN ISOLATION VALVE, INPUT DESIRED FUEL VOLUME INTO PRE-SET METER, AND SET SPRING LOADED MECHANICAL VALVE. UNWIND HOSE, PLACE NOZZLE IN APPROVED FUEL CONTAINER, DEPRESS PUMP START BUTTON TO PRESSURIZE HOSE, AND DEPRESS TRIGGER TO INITIATE FLOW. PROVIDE CONTINUOUS MONITORING DURING FUELING PROCESS. FLOW WILL AUTOMATICALLY STOP AT PRE-SET VOLUME, BUT PUMP WILL CONTINUE TO RUN. WHEN FUELING IS COMPLETE, DEPRESS PUMP STOP BUTTON, WIND HOSE ONTO REEL, HANG UP NOZZLE, AND NOTE VOLUME OF FUEL DISPENSED.








SCHEMATIC OPERATING

UPGRADES


BULK




Plot Date

Sheet No C2

TANK FARM OPERATING SCHEMATIC










	PILE	TABLE	
PILE NO.	NORTHING	EASTING	PILE SIZE
1	1072966.59	473251.53	HP 12x74
2	1072957.97	473256.61	HP 12x74
3	1072949.36	473261.68	HP 12x74
4	1072940.74	473266.75	HP 12x74
5	1072926.95	473274.87	HP 12x74
6	1072918.34	473279.95	HP 12x74
7	1072909.72	473285.02	HP 12x74
8	1072901.10	473290.10	HP 12x74
9	1072971.67	473260.15	HP 12x74
10	1072963.05	473265.22	HP 12x74
11	1072954.43	473270.30	HP 12x74
12	1072945.82	473275.37	HP 12x74
13	1072932.03	473283.49	HP 12x74
14	1072923.41	473288.57	HP 12x74
15	1072914.80	473293.64	HP 12x74
16	1072906.18	473298.71	HP 12x74
17	1072975.28	473266.28	HP 12x74
18	1072966.66	473271.35	HP 12x74
19	1072958.04	473276.43	HP 12x74
20	1072949.43	473281.50	HP 12x74
21	1072935.64	473289.62	HP 12x74
22	1072927.02	473294.70	HP 12x74
23	1072918.41	473299.77	HP 12x74
24	1072909.79	473304.84	HP 12x74
25	1072980.35	473274.89	HP 12x74
26	1072971.73	473279.97	HP 12x74
27	1072963.12	473285.04	HP 12x74
28	1072954.50	473290.12	HP 12x74
29	1072940.71	473298.24	HP 12x74
30	1072940.71	473303.31	HP 12x74
31	1072932.10	473308.39	HP 12x74
32	1072923.48	473313.46	HP 12x74
33	1072914.86	473281.02	HP 12x74
34	1072983.96	473286.10	HP 12x74
35	1072975.34	473291.17	HP 12x74
36	1072958.11	473291.17	HP 12x74
37	1072958.11		HP 12x74
38	1072944.32	473304.37 473309.44	HP 12x74
39	1072927.09	473314.51	HP 12x74
40	1072918.47	473319.59	HP 12x74
41	1072989.04	473289.64	HP 12x74
42	1072980.42	473294.72	HP 12x74
43	1072971.80	473299.79	HP 12x74
44	1072963.18	473304.87	HP 12x74
45	1072949.40	473312.98	HP 12x74
46	1072940.78	473318.06	HP 12x74
47	1072932.17	473323.13	HP 12x74
48	1072923.55	473328.21	HP 12x74
49	1072992.65	473295.77	HP 12x74
50	1072984.03	473300.85	HP 12x74
51	1072975.41	473305.92	HP 12x74
52	1072966.80	473311.00	HP 12x74
53	1072953.01	473319.11	HP 12x74
54	1072944.39	473324.19	HP 12x74
55	1072935.78	473329.26	HP 12x74
56	1072927.16	473334.34	HP 12x74
57	1072997.72	473304.39	HP 12x74
58	1072989.10	473309.46	HP 12x74
59	1072980.49	473314.54	HP 12x74
60	1072971.87	473319.61	HP 12x74
61	1072958.08	473327.73	HP 12x74
	1072949.47	473332.81	HP 12x74
62	10/2949.4/	1,,000=.0.	1115 124/7


	PILE	TABLE	
PILE NO.	NORTHING	EASTING	PILE SIZE
64	1072932.23	473342.96	HP 12x74
65	1072995.24	473324.97	HP 10x57
66	1072987.20	473329.71	HP 10x57
67	1072978.58	473334.78	HP 10x57
68	1072969.96	473339.86	HP 10x57
69	1072961.92	473344.59	HP 10x57
70	1072959.51	473348.75	HP 12x74
71	1072950.46	473354.08	HP 12x74
72	1072941.42	473359.41	HP 12x74
73	1072962.17	473353.27	HP 12x74
74	1072953.12	473358.60	HP 12x74
75	1072944.07	473363.92	HP 12x74
76	1073007.59	473345.95	HP 10x57
77	1072999.55	473350.68	HP 10x57
78	1072990.93	473355.76	HP 10x57
79	1072982.32	473360.83	HP 10x57
80	1072974.28	473365.57	HP 10x57
81	1073019.94	473366.92	HP 10x57
82	1073011.90	473371.66	HP 10x57
83	1073003.28	473376.73	HP 10x57
84	1072994.67	473381.81	HP 10x57
85	1072986.63	473386.54	HP 10x57
86	1073012.45	473314.75	HP 12x74
88	1072997.73	473326.90	HP 12x74
89	1073019.98	473327.53	HP 12x74
91	1073003.75	473337.09	HP 12x74
92	1073018.57	473402.68	HP 10x57
93	1073033.60	473418.36	HP 12x74
94	1073024.99	473423.44	HP 12x74
95	1073012.00	473336.18	HP 10x57
96	1073016.22	473345.24	HP 10x57
97	1073039.19	473323.50	HP 10x57
98	1073043.42	473332.57	HP 10x57
99	1073066.38	473310.83	HP 10x57
100	1073070.61	473319.90	HP 10x57
101	1073070.61	473298.15	HP 10x57
102	1073093.37	473307.21	HP 10x57
102	1073097.79	473284.45	HP 10x57
103	1073120.32	473294.45	
			HP 10x57
112	1073020.68	473425.98 473415.83	HP 12x74












# SPECIFIC NOTES


- 1 SHOP FABRICATED BOLT ON LADDER AND PLATFORM
- 2 3" MECHANICAL FILL LIMITER &DROP TUBE INSTALLED ON 6" FPT
- 3 4" THREADED PENETRATION (SPARE W/ PLUG)
- 2" THREADED PENETRATION (CLOCK 2)
  GAUGE INSTALLED ON 2" X 18"
- 5 2" FPT (GAUGE HATCH INSTALLED ON 2"X4" NIPPLE)
- 6 2" THREADED PENETRATION (WATER 3 C11)
- 7 3" FPT (3 POSITION LEVEL SWITCH)
- 8 24" MANHOLE
- 9 4" FPT (SUBMERSIBLE PUMP)
- 10" FLANGED PENETRATION (E-VENT, TYP 2)
- 3" FPT (3" PRESSURE VACUUM

  11> VENT WITH WHISTLE ALARM.) SET WHISTLE ALARM TO 90% FULL.
- 1" PRV (SELECT TANKS ONLY, SEE OP SCHEMATIC)

### GENERAL NOTES

- 1. TANKS ARE NEW, OWNER PROVIDED, DOUBLE WALL, UL 142 LISTED AND LABELED ASTs. SEE APPROVED SHOP DRAWINGS FOR ADDITIONAL DETAILS.
- 2. SEE SPECIFICATIONS & OP SCHEMATIC (SHEET C2) FOR FURTHER COMPONENT











FUEL UPGRADES GAL BULK

B H B H

Plot Date 7/28/21

Sheet No.

C9

**END VIEW** В

Α

**SECTION VIEW** 

2 2" MECHANICAL FILL LIMITER W/ DROP TUBE INSTALLED IN 4" FPT

3 4" THREADED PENETRATION (SPARE W/ PLUG)

2" THREADED PENETRATION (CLOCK GAUGE INSTALLED ON 2" X 18" NIPPLE)

5 2" FPT (GAUGE HATCH INSTALLED ON 2"X4" NIPPLE)

6 2" THREADED PENETRATION (WATER DRAW)

7> 3" FPT FOUR POSITION LEVEL SWITCHES

8 24" MANHOLE

9 4" FPT (SUBMERSIBLE PUMP)

10> 6" FLANGED PENETRATION (E-VENT)

11> 8" FLANGED PENETRATION (SECONDARY E-VENT)

3" THREADED PENETRATION (2" PRESSURE VACUUM VENT WITH WHISTLE ALARM.) INSTALL WITH 3"X2" REDUCING BUSHING & 2"X24" NIPPLE. SET WHISTLE ALARM TO 90% FULL.

13> 1" PRV

14> 2" CHECK VALVE

15> BALL VALVE


16> FLEXIBLE CONNECT

17> MOTOR ACTUATED BALL VALVE

### **GENERAL NOTES**


1. TANK IS NEW, OWNER PROVIDED, PROTECTED, UL 2085 LISTED AND LABELED AST. SEE APPROVED SHOP DRAWINGS FOR ADDITIONAL DETAILS.


2. SEE SPECIFICATIONS & OP SCHEMATIC (SHEET C2) FOR FURTHER COMPONENT REQUIREMENTS.



# 5,000 GALLON DUAL PRODUCT PROTECTED DISPENSING TANK -PLAN VIEW

**SECTION VIEW** 









GAL DOUBLE WALL PROTECTED DISPENSING TANK BULK FUEL UPGRADES

DATE 7/28/21 B H B H

Plot 7/28/21 Date 7/28/21

**END VIEW** 

SUBMERSIBLE PUMP ASSEMBLY

CLOCK GAUGE-SET GREEN - ARROW AT 50% LEVEL AND RED ARROW AT 90% LEVEL 2"X18" LONG NIPPLE AND COUPLING 3" SCH 40 STEEL PIPE, CENTER UNDER PENETRATION & INSTALL PLUMB — WELD TO TANK SHELL TOP ONLY 2" THREADED PENETRATION FOR GAUGE TOP OF TANK - CLOCK GAUGE FLOAT 1/2" WIDE x 6" LONG SLOTS ONE SIDE — FACE SLOTS AWAY FROM TANK HEAD (TYP 2) SLIP JOINT FOR EXPANSION 4" SCH 40 STEEL PIPE, CENTER UNDER BUNG — WELD TO TANK SHELL BOTTOM ONLY, CUT SLOTS AS SHOWN

BOTTOM OF TANK

INSERT 1" SCH 80 PIPE THROUGH FEMALE THREADS OF BUSHING AND FILLET
WELD PIPE TO BUSHING 1" MALE CAMLOCK W/ CAP P<sub>1/4</sub> 2"x1¼" FORGED STEEL - THREADED BUSHING (SIZE AS REQD @ SIM) EXTEND 1" PIPE TO WITHIN 1" OF TANK BOTTOM 2" PENETRATION (FIELD VERIFY SIZE @ SIM)

GAUGE FLOAT STILLING WELL 2

TYP WATER DRAW

### GENERAL NOTES

- 1. SEE SPECIFICATIONS FOR DETAILED COMPONENT DESIGNATIONS.
- 2. PROVIDE UL APPROVED GROUNDING LUG ON TANK SKIDS (TYP 2, ON OPPOSITE CORNERS)







TANK DETAILS BULK FUEL UPGRADES MISCELLANEOUS


DATE 7/28/21 ¥ B≼ FOR

Plot 7/28/21	Designed	Drawn	Approved

1

### DISPENSER NOTES

- PROVIDE PREFABRICATED PMC CG CABINET FUEL DISPENSER MODEL CG-515-MA. SEE SPECIFICAITONS FOR ADDITIONAL DETAILS AND REQUIRED DISPENSING APPURTENANCES. SEE MANUFACTURERS CUT SHEETS FOR MOUNTING AND PIPING DIMENSIONS.
- 2. SUBMIT SHOP DRAWINGS FOR LIQUID TIGHT DISPENSER BASE.
  3. SEE ELECTRICAL FOR CONTROLS.



HOSE REEL DISPENSER ELEVATION VIEW

EQUIP WITH ARCTIC HOSE, NOZZLE, ETC. (SEE SPECIFICATIONS)

HOSE REEL DISPENSER FRONT VIEW & SUMP









DISPENSER UPGRADES FUEL REEL BULK






TYPICAL BEAM & PILE

CAP, SEE STRUCTURAL




1. ALL HP12 PILES SHALL BE EMBEDDED 45' MIN & ALL HP10 PILES SHALL BE EMBEDDED 37' MIN.

SCALE: NTS



# **TYPICAL P1 PILE SECTION** SCALE: NTS



# THERMOSIPHON SLEEVE END SCALE: NTS

# THERMOSIPHON SLEEVE END

SCALE: NTS

### THERMOSIPHON NOTES:

- 1. SEE SPECIFICATIONS FOR OWNER FURNISHED MATERIALS.
  THERMOSIPHON SLEEVES ARE TO BE FABRICATED AND WELDED
- TO THE PILES BY THE CONTRACTOR.

  2. INSTALL THERMOSIPHONS & PILE SLEEVES AT LOCATIONS SHOWN ON THE PILE LAYOUT PLAN.
- 3. INSTALL THERMOSIPHONS ON PILES ADJACENT TO THE JOHNSON RIVER (TYP 4)

PASSIVE COOLING— THERMOPROBES
THERMOPROBES TO BE DESIGNED BY ARCTIC FOUNDATION INC., TO THE FOLLOWING SPECIFICATIONS:

EVAPORATOR: 1.5" DIAMETER CONDENSER AREA: 35 SQFT MIN EMBEDMENT DEPTH: 35 FT







DETAILS PILE AND THERMOSIPHON

UPGRADES

BULK


DATE 7/28/21 PH B≺


Sheet No. C13

TYPICAL PILE INSTALLATION

CJP IF SPLICED

THERMOSIPHON CONDENSER, 35 SF






PIPE SUPPORT

INSTALLED SO THAT THE SPRING WASHER

SMALL PIECE OF 3"x3" ANGLE STEEL IS TO BE WELDED ONTO PILING TO

FOR ITS ENTIRE LENGTH. TIGHTEN BOLTS SEQUENTIALLY AND EVENLY. BOLTS SHALL BE TIGHTENED WITH THE COMPRESSED AND THE SQUARE WASHER AND PILING FLANGE INDENTED INTO THE



ITEM	QTY.	MATERIAL
а	1	10x57x HP STEEL PILING
Ь	8	SPRING CLIP WASHER, 3/4"
С	4	BOLT, WASHER, 3/4" x REQ'D LENGTH
d	4	WASHER, SQ. CURVED, 4"x4" W/ 13/16" HOLE
е	4	LOCKNUT, 3/4" MF TYPE
f	4	SPRING CLIP WASHER, 5/8"
g	4	BOLT, MACHINE, 5/8" x REQ'D LENGTH
h	8	WASHER, SQ. CURVED, 4"x4" W/ 11/16" HOLE
i	4	LOCKNUT, 5/8" MF TYPE
j	4	WASHER, SQ., 2-1/4"x2-1/4" W/ 13/16" HOLE

**ELECTRICAL POLE TO PILE** 





DETAILS MISCELLANEOUS

UPGRADES

FUEL

BULK

DATE 7/28/21 F B

NOT REQUIRED

EXITS REQUIRED: PANIC HARDWARE:

NOT REQUIRED


EXIT SEPARATION: EXIT TRAVEL DISTANCE: GREATER THAN ½ OF THE LONGEST DIAGONAL DISTANCE 200 FT MAXIMUM WITHOUT SPRINKLER SYSTEM

NOT REQUIRED

FIRE BLOCKING: FIRE ALARM: FIRE SUPPRESSION SYSTEM:

SMOKE ALARMS:

NOT REQUIRED NOT REQUIRED




- CONNEX DOORS TO REMAIN LOCKED OPEN DURING BUILDING USE.
   SEE ELECTRICAL FOR WIRING AND BASEBOARD HEAT.

### CONNEX INSULATION AND INTERIOR SURFACE CONSTRUCTION SEQUENCE:

- 1. BOND DOW HI-40 RIGID INSULATION TO CONNEX ROOF (2 LAYERS @ 2" EA) AND WALLS (1 LAYER @ 2") WITH OSI QB-300 CONSTRUCTION ADHESIVE.
  2. TAPE ALL INSULATION JOINTS WITH TYVEK TAPE.
- 3. BOND 56" T&G PLYWOOD TO INSULATION WITH OSI QB-300 CONSTRUCTION ADHESIVE.
  4. TEK SCREW OR BOLT PLYWOOD & INSULATION TO CONNEX AT 24" OC EA WAY.
  5. APPLY A FLEXIBLE ROOF SEALENT TO ALL ROOF AND WALL PENETRATIONS.

- 6. PRIME AND PAINT PLYWOOD WHITE.

UNDERSIDE OF CONNEX:
1. APPLY URETHANE SPRAY FOAM TO THE UNDERSIDE OF CONNEX (4" MIN.) TOP COAT WITH SWD URETHANE QUICK-SHIELD 951, OAE.




**PARTITION SECTION** 






FUEL UPGRADES UPGRADES CONNEX BULK

ISSUED FOR BIDDING AH 7/28/21					
_		7/28/21			
REVISION ISSUED FOR BIDDING	B	ΑH			
	REVISION	ISSUED FOR BIDDING			





NOTE:

TENSION BARS SHALL BE INSTALLED CONTINUOUSLY FROM TOP RAIL TO BOTTOM OF FENCE.

FENCE BRACING DETAIL 2

### FENCE NOTES:

- 1. FENCE POST HOLES ARE TO BE PRE-DRILLED AS REQUIRED WHERE FROZEN GROUND IS ENCOUNTERED.
- 2.DRIVE CORNER AND GATE POSTS TO A DEPTH OF 10-FEET & LINE POSTS TO A DEPTH OF 8-FEET BELOW
- 3. ATTACH FENCE TO PLATFORM IN AREAS SHOWN (SEE STRUCTURAL DETAILS).
- 4. SEE SITE PLAN FOR FENCE LAYOUT.
- 5. SEE FENCE DETAIL SHEET FOR GATE DETAILS.
- 6.FENCE POSTS SHALL NOT BE INSTALLED UNTIL FENCE ROUTE & GATE LOCATIONS ARE STAKED OUT AND APPROVED BY ENGINEER.
- 7. SEE DETAIL THIS SHEET FOR TOP RAIL SLEEVE.
- 8.SEE ELECTRICAL FOR FENCE GROUNDING.







DETAILS

UPGRADES

BULK

H B

INSTALL ALUMINUM ANGLE BRACKET TO CONNECT FLAT BAR CUT BACK WIRE FABRIC AND WEAVE 1"X1/8" ALUMINUM FLAT BAR THROUGH WIRE FABRIC PIPE OR CONDUIT 4" MAX

FENCE PENETRATION DETAIL

2

**GATE INSTALLATION DETAIL** 


GATE CORNER


GALV. OR ALUM.

# GATE NOTES:

- 1. THREE (3) HINGES SHALL BE INSTALLED PER GATE. THE TOP TWO (2) SHALL BE INSTALLED WITH HINGE PINS SUPPORTING GATE. (GATE PORTION OF HINGE ON TOP.) THE LOWEST HINGE SHALL BE INSTALLED WITH GATE PORTION ON BOTTOM TO PREVENT MOVEMENT OF GATES.

  2. COORDINATE GATES LOCATED ON THE STEEL PLATFORM WITH STRUCTURAL
- DRAWINGS TO ENSURE CLEARANCE TO DECK AND HANDRAIL.





LATCH DETAIL

**GATE HINGE DETAIL** 5 NTS





BULK FUEL UPGRADES DETAILS FENCE

DATE 7/28/21 B H B H

Plot Date 7/28, C17

POST LOCATIONS AT GATE

NTS

FLOOR LL=40 PSF (CONSTRUCTION LIVE LOAD=20 PSF)
SEISMIC DESIGN CATEGORY C, SITE CLASS D (IBC), I-1.25
3 SEC WIND GUST=155 MPH EXPOSURE C

2. EXISTING STRUCTURES

THESE CONSTRUCTION DOCUMENTS HAVE BEEN PREPARED BASED ON LIMITED VISUAL OBSERVATIONS AND/OR LIMITED AS—BUILT DOCUMENTS. CHANGES MAY BE REQUIRED DUE TO POSSIBLE AMBIGUITIES OR INCONSISTENCIES IN RECORD DRAWINGS.

VERIFY ALL EXISTING DIMENSIONS, MEMBER SIZES AND CONDITIONS PRIOR TO COMMENCING ANY WORK. ALL DIMENSIONS OF EXISTING CONSTRUCTION SHOWN ON THE DRAWINGS ARE INTENDED AS GUIDELINES ONLY AND MUST BE VERIFIED.

IF FIELD CONDITIONS DIFFER FROM THOSE DEPICTED OR EXISTING MATERIALS ARE OF QUESTIONABLE OR SUBSTANDARD QUALITY, NOTIFY THE STRUCTURAL ENGINEER IN WRITING BEFORE COMMENCING ANY WORK. THE CONTRACTOR SHALL REPORT ALL DIFFERENCES AND DEFECTS PROMPTLY.

3. FOUNDATION AND EARTHWORK

REFERENCE GEOTECHNICAL REPORT NO. 18105833, BY GOLDER, DATED 31 MAY 2019 FOR DEEP FOUNDATION INFORMATION.

THE STRUCTURAL ENGINEER IS NOT RESPONSIBLE FOR ANY GEOTECHNICAL ASPECTS OF THIS PROJECT. THE OWNER SHALL EMPLOY A REGISTERED GEOTECHNICAL ENGINEER TO PERFORM NECESSARY EARTHWORK INSPECTIONS, TESTING AND QUALITY CONTROL, AS REQUIRED.

- 4. STRUCTURAL STEEL SHALL BE DETAILED, FABRICATED, AND ERECTED ACCORDING TO THE AMERICAN INSTITUTE OF STEEL CONSTRUCTION "AISC MANUAL", 14TH EDITION. STRUCTURAL STEEL SHALL CONFORM TO ASTM A—36. STRUCTURAL TUBING IN ROUNDS OR SHAPES SHALL BE ASTM A—500. BOLTS SHALL BE 3/4"—INCH DIAMETER, UNLESS INDICATED OTHERWISE, ASTM A—307, EDGE DISTANCES SHALL BE NOT LESS THAN MINIMUMS SPECIFIED BY AISC. ALL WELDS SHALL COMPLY WITH THE CURRENT EDITION OF ANSI/AWS D1.1 AND MADE BY CERTIFIED WELDERS USING ELECTRODES CONFORMING TO ASTM A153 HOT—DIP PROCESS. PROVIDE SHOP DRAWINGS WITH DETAILS FOR REVIEW PRIOR TO FABRICATION. ALL STEEL TO STEEL BOLTED CONNECTIONS SHALL BE WITH HIGH STRENGTH TENSION CONTROL BOLTS, UNO MIN. OF (2) BOLTS PER CONNECTION.
- 5. SHOP DRAWINGS: THE CONTRACTOR SHALL REVIEW, STAMP WITH HIS APPROVAL, DATE, AND SIGN ALL SHOP DRAWINGS REQUIRED BY THE ENGINEER. AT THE TIME OF SUBMISSION, THE CONTRACTOR SHALL INFORM THE ENGINEER IN WRITING OF ANY DEVIATION IN THE SHOP DRAWINGS FROM THE REQUIREMENTS OF THE CONTRACT DOCUMENTS. SUBMITTALS SHALL INCLUDE ITEMS OUTLINED IN THE CONSTRUCTION DOCUMENTS.
- 6. ALL EXPOSED SURFACES ON STRUCTURAL STEEL SHALL BE HOT DIP GALVANIZED. ALL WELDS SHALL BE CLEANED AND PAINTED OVER WITH A COLD GALVANIZING COATING WITH A MINIMUM OF 95% ZINC PER THE MANUFACTURER'S RECOMMENDATIONS.
- 7. STRUCTURAL MATERIALS:

HP SECTIONS
W-SECTIONS
CHANNELS, ANGLES, PLATES, ETS.:
STEEL PIPES:
BOLTS:
HARDENED WASHERS:

ASTM A 53 ASTM F 307 GRADE A ASTM F 436 ASTM A 563 (GRADE OF NUT

ASTM A 572 GR. 50

ASTM A 992

ASTM A 36

SHALL MATCH BOLT MATERIAL)

- 8. THE CONTRACTOR SHALL VERIFY AND COORDINATE ALL DIMENSIONS AMONG THE DRAWINGS BEFORE STARTING ANY WORK OR FABRICATION. ANY DISCREPANCIES FOUND AMONG THE DRAWINGS, SITE CONDITIONS, SPECIFICATIONS AND THESE NOTES SHALL BE REPORTED TO THE ENGINEER AT ONCE.
- ALL CONSTRUCTION SHALL COMPLY WITH THE INTERNATIONAL BUILDING CODE 2012 (I.B.C. 2012).

10. SAFETY — THE STRUCTURAL ENGINEER HAS NOT BEEN RETAINED OR COMPENSATED TO PROVIDE DESIGN AND/OR CONSTRUCTION REVIEW SERVICES RELATED TO THE CONTRACTOR'S SAFETY PRECAUTIONS OR TO MEANS, METHODS, TECHNIQUES, SEQUENCES OR PROCEDURES FOR THE CONTRACTOR TO PERFORM HIS WORK. THE UNDERTAKING OF PERIODIC SITE VISITS BY THE ENGINEER SHALL NOT BE CONSTRUED AS SUPERVISION OF ACTUAL CONSTRUCTION NOR MAKE THEM RESPONSIBLE FOR PROVIDING A SAFE PLACE FOR THE PERFORMANCE OF WORK BY THE CONTRACTOR, SUBCONTRACTORS, SUPPLIERS OR THEIR EMPLOYEES, OR FOR ACCESS, VISITS, USE, WORK, TRAVEL OR OCCUPANCY BY ANY PERSON.

DRAWINGS INDICATE STRUCTURE IN FINAL FORM CAPABLE OF SUPPORTING DESIGN LOADS. PROVIDE TEMPORARY SUPPORT DURING CONSTRUCTION AS REQUIRED, UNTIL STRUCTURAL ELEMENTS ARE PERMANENTLY INSTALLED. THE CONTRACTOR SHALL BE RESPONSIBLE FOR ALL SAFETY PRECAUTIONS AND THE METHODS, TECHNIQUES AND SEQUENCES OF PROCEDURES REQUIRED TO PERFORM THE WORK.

THE CONTRACTOR SHALL IMMEDIATELY NOTIFY THE STRUCTURAL ENGINEER IN WRITING OF ANY CONDITION WHICH IN THEIR OPINION MAY ENTRY THE STABILITY OF THE STRUCTURE OR DISTRESS THE STRUCTURE.

CONSTRUCTION MATERIALS SHALL BE DISTRIBUTED APPROPRIATELY IF PLACED ON FRAMED CONSTRUCTION. LOADS SHALL NOT EXCEED THE DESIGN LIVE LOAD PER SQUARE FOOT.

DO NOT SCALE DRAWINGS.

THE CONTRACTOR SHALL VERIFY ALL DIMENSIONS, ELEVATIONS, AND SITE CONDITIONS BEFORE STARTING WORK. THE CONTRACTOR SHALL IMMEDIATELY NOTIFY THE ARCHITECT AND STRUCTURAL ENGINEER IN WRITING OF ANY DISCREPANCIES.

COORDINATE DIMENSIONS, OPENINGS, EMBEDDED ITEMS, AND CONDITIONS WITH ARCHITECTURAL, CIVIL, MECHANICAL, AND ELECTRICAL CONTRACT DOCUMENTS, AND TRADES PRIOR TO CONSTRUCTION. NOT ALL ITEMS ARE INDICATED ON STRUCTURAL CONTRACT DOCUMENTS. NOTIFY STRUCTURAL ENGINEER IN WRITING OF ANY AND ALL DISCREPANCIES.

ALL DETAILS ARE TYPICAL. INCORPORATE INTO PROJECT AT APPROPRIATE LOCATIONS WHETHER SPECIFICALLY INDICATED OR NOT.

SPECIFIC NOTES AND DETAILS SHALL TAKE PRECEDENCE OVER GENERAL NOTES AND TYPICAL DETAILS. WHERE THE NOTES, DRAWINGS, AND/OR SPECIFICATIONS DIFFER, THE MORE STRINGENT REQUIREMENTS SHALL APPLY

REFER TO CIVIL DRAWINGS FOR EXTERIOR FENCES AND WALLS.

NOTIFY STRUCTURAL ENGINEER OF ALL FIELD CHANGES PRIOR TO INSTALLATION.

THE CONTRACTOR SHALL MAINTAIN A CURRENT SET OF RED-LINED DRAWINGS ON SITE REFLECTING ALL DESIGN CHANGES TO THE ORIGINAL CONTRACT DOCUMENTS.

- 11. GRATING SHALL BE 19-W-4, GRATING PACIFIC 1-3/x3/6 STEEL GRATING, OR EQUAL. MATERIAL SHALL BE GALV. STEEL GRATING SHALL SAFELY SUPPORT A SUSTAINED UNIFORM LOAD OF 100 PSF ON A SPAN OF 5'-0", WITH LESS THAN 0.5" DEFLECTION.
- 12. MODULAR GUARDRAILS SHALL BE KEE SAFETY TYPE GUARDRAILS MANUFACTURED OUT OF GALVANIZED STEEL TO SUPPORT HANDRAIL LOADING (SEE BELOW) OR EQUIVALENT. PROVIDE GUARDRAILS WITH THE KEE KLAMP SYSTEM. CONTRACTORS OPTION TO SUBMIT ALTERNATIVE MODULAR OR FABRICATED HANDRAILS CAPABLE OF SUPPORTING 50 PLF OR A 200 LB LATERAL AT 36" ABOVE THE BASE.

	ABBREVIATIONS		ABBREVIATIONS
E)	EXISTING	LSL	LAMINATED STRAND LUMBER
N)	NEW	LVL	LAMINATED VENEER LUMBER
AB	ANCHOR	LWC	LIGHT WEIGHT CONCRETE
ACI	AMERICAN CONCRETE INSTITUTE	MAX	MAXIMUM
AISC	AMERICAN INSTITUTE OF STEEL	MCJ	MASONRY CONTROL JOINT
A I C I	CONSTRUCTION	MECH	MECHANICAL
AISI	AMERICAN IRON AND STEEL INSTITUTE	MIN	MINIMUM
ALT	ALTERNATE	MRF('S)	MANUFACTURER('S)
ASCE	AMERICAN SOCIETY OF CIVIL	MT	MAGNETIC PARTICLE TESTING
NOOL	ENGINEERS	N/A	NOT APPLICABLE
ASD	ALLOWABLE STRESS DESIGN	NIC	NOT IN CONTRACT
STM	AMERICAN SOCIETY FOR TESTING	NTS	NOT TO SCALE
	AND MATERIALS	NWC	NORMAL WEIGHT CONCRETE
WPA	AMERICAN WOOD PROTECTION	0C	ON CENTER
	ASSOCIATION	OPP	OPPOSITE (MIRRORED)
WS	AMERICAN WELDING SOCIETY	PAF PC	POWDER ACTUATED FASTENER PILE CAP
M	BEAM	PCC	PRECAST CONCRETE
OB	BOTTOM OF BEAM	PEMB	PRE-ENGINEERED METAL
OD	BOTTOM OF DECK	FLIVID	BUILDING
OF	BOTTOM OF FOUNDATION	PJP	PARTIAL JOINT PENETRATION
0S	BOTTOM OF STEEL	PL	PLATE
OT ••C	BOTTOM	PLF	POUNDS PER LINEAR FOOT
&C	COMPONENTS AND CLADDING	PREFAB	PREFABRICATED
FS IP	COLD-FORMED STEEL CAST-IN-PLACE	PSF	POUNDS PER SQUARE FOOT
J J		PSI	POUNDS PER SQUARE INCH
J JP	CONTROL JOINT COMPLETE JOINT PENETRATION	PT	POINT
JP L	COMPLETE JOINT PENETRATION  CENTERLINE	QA	QUALITY ASSURANCE
L LR	CLEAR	QC	QUALITY CONTROL
MU	CONCRETE MASONRY UNIT	R	RADIUS
OL	COLUMN	REINF	REINFORCED/REINFORCING
OMP	COMPRESSIVE	RT	RADIOGRAPHIC TESTING
ONC	CONCRETE	SC	SLIP CRITICAL
ONN	CONNECTION	SCH	SCHEDULE
ONT	CONTINUOUS	SDI	STEEL DECK INSTITUTE
RSI	CONCRETE REINFORCING STEEL	SEC	SECOND
	INSTITUTE	SECT	SECTION
ET	DETAIL	SF	SQUARE FOOT
F	DOUGLAS-FIR	SHT	SHEET
IA	DIAMETER	SIM	SIMILAR
IM(S)	DIMENSION(S)	SIP	STRUCTURAL INSULATED PANEL
L	DEAD LOAD	SLH	SHORT LEG HORIZONTAL
N	DOWN	SLRS	SEISMIC LOAD RESISTING SYSTE
WG(S)	DRAWING(S)	SLV	SHORT LEG VERTICAL
Α	EACH	SOG	SLAB ON GRADE
J	EXPANSION JOINT	SP	SPACE
Q	EQUAL	SPF	SPRUCE-PINE-FIR
QUIP	EQUIPMENT	SQ	SQUARE
SR	EVALUATION SERVICE REPORT	SS	STAINLESS STEEL
W	EACH WAY	STD	STANDARD
FE	FINISHED FLOOR ELEVATION	STIFF	STIFFENER
PSF	FROST PROTECTED SHALLOW	STL	STEEL
	FOUNDATION	STR	STRUCTURAL
S	FROST SUSCEPTIBLE	SUP	SUPPORT
T	FOOT OR FEET	SYM	SYMMETRICAL
TG	FOOTING	T&B	TOP AND BOTTOM
A	GAUGE	TG	TRUSS GIRDER
ALV	GALVANIZED	THK	THICK OR THICKNESS
В	GRADE BEAM	THRD	THREADED
LB	GLUE-LAMINATED BEAM	TL	TOTAL LOAD
P B	GUSSET PLATE	TOB TOC	TOP OF BEAM TOP OF CONCRETE
R	GRADE		
SN	GENERAL STRUCTURAL NOTES	TOD	TOP OF DECK TOP OF FOUNDATION
F	HEM-FIR	TOF TOM	TOP OF FOUNDATION TOP OF MASONRY
OR S	HORIZONTAL	TOP	TOP OF PLATE
SS	HIGH STRENGTH HOLLOW STRUCTURAL SECTION	TOS	TOP OF PLATE
3C	INTERNATIONAL BUILDING CODE	TOW	TOP OF WALL
CC	INTERNATIONAL BUILDING CODE	TRANS	TRANSVERSE
DF	INSULATED CONCRETE FORM	TYP	TYPICAL
BC	INTERNATIONAL EXISTING	UNO	UNLESS NOTED OTHERWISE
	BUILDING CODE	UT	ULTRASONIC TESTING
١	INCH	VERT	VERTICAL
, T	JOINT	VSC2	VERCO SIDELAP CONNECTION
	KIP (1000 POUNDS)	W/	WITH
SI	KIPS PER SQUARE INCH	W/C	WATER-TO-CEMENT
BS	POUNDS	W/C W/O	WITHOUT
	LIVE LOAD	W/O WP	WORKING POINT
L	LONG LEG HORIZONTAL	WPS('S)	WELDING PROCEDURE
		111 3(3)	SPECIFICATION(S)
LH	LONG LEG VERTICAL		
L LH LV ONG	LONG LEG VERTICAL LONGITUDINAL	WSP	WOOD STRUCTURAL PANEL
LH LV	LONG LEG VERTICAL LONGITUDINAL LOAD AND RESISTANCE	WSP WWF	WOOD STRUCTURAL PANEL WELDED WIRE
LH LV ONG	LONGITUDINAL		





GENERAL STRUCTURAL NOTES

UPGRADES

FUEL


BULK


ISSUED FOR BIDDING

AH 7/28/21

Plot 7/28/21
Designed \_\_\_\_
Drawn \_\_\_
Approved \_\_\_


Sheet No.
















STEEL BEAM AT STEEL BEAM

STEEL GRATING AT STEEL BEAM

STEEL BEAM Connection at Steel Pile





STEEL VEHICLE RAIL AT STEEL BEAM

STEEL BEAM AT STEEL BEAM

ALASKA ENERGY AUTHORIT







BULK FUEL UPGRADES
BEAM CONNECTION DETAILS

ISSUED FOR BIDDING AH 7/28/21

Plot 7/28/21
Designed \_\_\_\_
Drawn \_\_\_

Sheet No.










BEAM CONNECTION DETAILS BULK FUEL UPGRADES

BY DATE AH 7/28/21

Plot 7/28/21 Date 7/28/21

Sheet No.





		FIXTURE	SCHEDULE	
SYMBOL	LAMP SIZE	MOUNTING	DESCRIPTION	MANUFACTURER
•	50W LED	POLE: (LIGHT POLES PLUS) VS-SSEH-25-6437-11-AB-F P-WH-D2, OR EQUAL	50W LED WITH 6' MOUNTING ARM, -40F RATED, AND PHOTOCELL  ALL OTHER LOCATIONS	POWER SECURE HAWKLITE: #HL1-5-3M-740-STD-0-10-GY-6P WITH LITHONIA SMAWT2OUS6 ARM  POWER SECURE HAWKLITE: #HL1-5-3M-740-STD-0-10-GY-6P WITH LITHONIA SMAC ARM
- <del>(</del> A)-	25W LED	BRACKET MOUNTED	VAPORTITE L.E.D AREA LIGHT SURFACE MOUNT.	LITHONIA LIGHTING: TDD LED AREA LIGHT
	50W LED	POLE: (LIGHT POLES PLUS) VS-SSEH-25-6437-11-AB-F P-WH-D2, OR EQUAL	CLASS 1, DIV. 2.  VAPORTITE L.E.D AREA LIGHT SURFACE MOUNT. CLASS 1, DIV. 2.	LITHONIA LIGHTING: RSXF1-LED-P1-40K-WFL-MVOLT-AASP

	ELECTRICAL EQUIPMENT SCHEDU	JLE
ITEM NO.	DESCRIPTION	MANUFACTURER
$\bigcirc$	EMERGENCY SHUTOFF SWITCH. 4 DIE—CAST ALUMINUM ENCLOSURE, 2-1/4" DIA. RED MUSHROOM HEAD MAINTAINED CONTACT PUSH BUTTON WITH 1 EA. NC CONTACT, 10A RATED.	ALLEN BRADLEY 800T—FX6D4 WITH 800T—1TZ ENCLOSURE & 800T—N247R HEAD
2>		P&S 2095TRWRI RED DOT CCGV COVER RED DOT IH32LM BO
3	LIGHT SWITCH AND RECEPTACLE. COMPLETE WITH 20A, 125V DUPLEX GFCI RECEPTACLE, 20A SINGLE POLE SWITCH. INSTALL IN CAST MULTI-GANG FD BOX WITH WEATHERPROOF COVER.	P&S 2095TRWRI RECEPTACLE P&S PS20AC1—I SWITCH RED DOT 2CCTG COVER RED DOT 2IH4—2 BOX
4	LOCKABLE SWITCH. 4, 7, 9 EXPLOSION PROOF CONSTRUCTION WITH 3/4" FEED THRU HUB, 4PST, 250V, 20A.	KILLARK
\$	FOUR POSITION FLOAT ACTIVATED LEVEL SWITCH, 316 SS STEM, 2" 316 SS FLOAT, 2" NPT BUSHING, 1/2" NPT CONDUIT ENTRY, EXPLOSION PROOF CONSTRUCTION, LISTED FOR CLASS 1, DIVISION 1, GROUP D, 120VAC, 100W MAX SWITCHING POWER. PROVIDE FLOAT ACTIVATED SWITCHES AT DIMENSIONS BASED ON APPROVED SHOP DRAWINGS CONTRACTOR SHALL VERIFY ACTUAL TANK DIMENSIONS AND SUBMIT SWITCH DIMENSIONS TO CONSTRUCTION MANAGER FOR APPROVAL PRIOR TO ORDERING.	CUSTOM SWITCHES, INC. MODEL LS-1900 TYPE 8 OR APPROVED EQUAL CONTRACTOR TO VERIFY CUSTOM PROBLENGTHS PRIOR TO ORDERING. SEE DESCRIPTION.
6	THREE POSITION FLOAT ACTIVATED LEVEL SWITCH, 316 SS STEM, 2" 316 SS FLOAT, 2" NPT BUSHING, 1/2" NPT CONDUIT ENTRY, EXPLOSION PROOF CONSTRUCTION, LISTED FOR CLASS 1, DIVISION 1, GROUP D, 120VAC, 100W MAX SWITCHING POWER. PROVIDE FLOAT ACTIVATED SWITCHES AT DIMENSIONS BASED ON APPROVED SHOP DRAWINGS. CONTRACTOR SHALL VERIFY ACTUAL TANK DIMENSIONS AND SUBMIT SWITCH DIMENSIONS TO CONSTRUCTION MANAGER FOR APPROVAL PRIOR TO ORDERING.	CUSTOM SWITCHES, INC. MODEL LS—1900 TYPE 7 OR APPROVED EQUAL CONTRACTOR TO VERIFY CUSTOM PROBLENGTHS PRIOR TO ORDERING. SEE DESCRIPTION.
$\Diamond$	LIQUID LEVEL MONITOR SYSTEM FOR AVEC DIESEL TANKS	PANEL: FRANKLIN FUEL, SYSTEM EV0550, PROBE: FRANKLIN FMP-LL3-137-1, PROBE: INSTALL KIT TSP-C2A, FLOAT: TSP-IDF2 (2" FOR DIESEL), CABLE TO PROBE: BELDEN #89182







ABBREVIATI ઝ LEGEND, NOTES,

UPGRADES

FUEL

BULK

돌

Plot Date

Sheet No.

LOCATIO	N: SPII	LL RESPONSE EQUIPMENT KIOSK		20	8Y/12	OV		3ф, 4 WIRE	10,	000 AIC
SERVED	FROM:	MAIN BREAKER		20	M AOC	LO			١	NEMA 3F
POLE	AMP	LOAD	POLE				POLE	LOAD	AMP	POLE
#	TRIP	DESCRIPTION	kVA	Аф	Вφ	Сф	Kva	DESCRIPTION	TRIP	#
1	40/2	CD 1	3.7	4.1			0.4	TANK FARM LIGHTING	20/1	2
3	40/2		3.3		3.7		0.4	PLATFORM LIGHTING	20/1	4
5	20/1	SALES CONNEX LIGHTING	0.2			0.4	0.2	CONNEX EXTERIOR LIGHTING	20/1	6
7	20/1	HOSE REEL LIGHTING	0.2	0.7			0.5	CONNEX RECEPTACLES	20/1	8
9	20/1	CONNEX HEATER	1.5		3.5		2.0	MOTOR STARTERS	90/2	10
11	20/1	SPILL RESPONSE CONNEX LIGHTING	0.2			2.2	2.0	-MOTOR STARTERS	90/2	12
13	20/1	HOSE REEL WINDING MOTOR	0.9	0.9			0.0	SPARE	20/1	14
15		SPACE	0.0		0.0		0.0	SPACE		16
17		SPACE	0.0			0.0	0.0	SPACE		18
			•	4.8	7.2	2.6		Total kVA	14.6	kVA



(1) 3/4"X10' COOPER CLAD STEEL GROUND RODS CONNECTED WITH #2 BCU.



- $\begin{tabular}{lll} \hline $\langle \end{tabular} & 3 \end{tabular}$  100A, 120/240V, 1 $\phi$ , 3 WIRE, 12 SPACE, NEMA 4X LOAD CENTER.
- (4) PROVIDE ARC FLASH WARNING PLACARD TO READ "AIC RATING OF X,XXX A CALCULATED ON X/X/2020." PROVIDE PPE LABLE FOR LEVEL 1 PER NFPA 70E.
- $\langle 5 \rangle$  PROVIDE STUB POLE
- 6 SEE SHEET E6 FOR CONDUIT DEVELOPMENT PLAN

[X-XXX] SEE SHEET E4 FOR CONDUIT SCHEDULE








PANEL DIAGRAM AND F SCHEDULE -LINE

BULK FUEL UPGRADES

	DATE				
	ВУ				
	REVISION				
	NO.				

Sheet No.



CON	DUIT	CONDUCTO	ORS	FROM	ТО	REMARKS
NO.	SIZE	POWER	SPARES*			
P-100	1	3#8, 1#8GND		PANEL A	CP-1	
P-101	3/4	2#12, 1#12GND		P4	JB-P-1	
P-102	3/4	2#12, 1#12GND		P3	JB-P-1	
P-103	3/4	4#12, 1#12GND		JB-P-1	JB-P-2	
P-104	3/4	2#12, 1#12GND		P-2	JB-P-2	
P-105	3/4	6#12, 1#12GND		JB-P-2	JB-P-3	
P-106	3/4	2#12, 1#12GND		P1	JB-P-3	
P-107	3/4	8#12, 1#12GND		JB-P-3	MS WIREWAY	
P-108	3/4	2#12, 1#12GND		MS WIREWAY	MS-P4	P-4 TO MS-P4
P-109	3/4	2#12, 1#12GND		MS WIREWAY	MS-P3	P-3 TO MS-P3
P-110	3/4	2#12, 1#12GND		MS WIREWAY	MS-P2	P-2 TO MS-P2
P-111	3/4	2#12, 1#12GND		MS WIREWAY	MS-P	P-1 TO MS-P1
P-112	3/4	2#12, 1#12GND		MS-P4	PANEL A WIREWAY	
P-113	3/4	2#12, 1#12GND		MS-P3	PANEL A WIREWAY	
P-114	3/4	2#12, 1#12GND		MS-P2	PANEL A WIREWAY	
P-115	3/4	2#12, 1#12GND		MS-P1	PANEL A WIREWAY	11
P-116	3/4	2#12, 1#12GND		P8	JB-P-4	
P-117	3/4	2#12, 1#12GND		P7	JB-P-4	
P-118	3/4	4#12, 1#12GND		JB-P-4	JB-P-5	
P-119	3/4	2#12, 1#12GND		P-6	JB-P-5	
P-120	3/4	6#12, 1#12GND		JB-P-5	JB-P-6	
P-121	3/4	2#12, 1#12GND		P5	JB-P-6	
P-122	3/4	8#12, 1#12GND		JB-P-6	MS WIREWAY	
P-123	3/4	2#12, 1#12GND		MS WIREWAY	MS-P8	P-8 TO MS-P8
P-124	3/4	2#12, 1#12GND		MS WIREWAY	MS-P7	P-7 TO MS-P7
P-125	3/4	2#12, 1#12GND		MS WIREWAY	MS-P6	P-6 TP MS-P6
P-126	3/4	2#12, 1#12GND		MS WIREWAY	MS-P5	P-5 TO MS-P5
P-127	3/4	2#12, 1#12GND		MS-P8	PANEL A WIREWAY	
P-128	3/4	2#12, 1#12GND		MS-P7	PANEL A WIREWAY	
P-129	3/4	2#12, 1#12GND		MS-P6	PANEL A WIREWAY	
P-130	3/4	2#12, 1#12GND		MS-P5	PANEL A WIREWAY	
P-131	3/4	2#12, 1#12GND		P-9A	JB-P-7	
P-132	3/4	2#12, 1#12GND	1	P-9B	JB-P-7	
P-133	3/4	4#12, 1#12GND		JB-P-7	JB-P-8	
P-134	3/4	4#12, 1#12GND	1	JB-P-8	MS WIREWAY	11
P-135	3/4	2#12, 1#12GND	1	MS WIREWAY	MS-P9A	P-9A TO MS-P9A
P-136	3/4	2#12, 1#12GND	11	MS WIREWAY	MS-P9B	P-9B TO MS-P9B
P-137	3/4	2#12, 1#12GND	1	MS-P9A	PANEL A WIREWAY	1
P-138	3/4	2#12, 1#12GND	1	MS-P9B	PANEL A WIREWAY	11
P-139	3/4	2#12, 1#12GND	1	PANEL A WIREWAY	PANEL A	11
P-140	3/4	2#12, 1#12GND	1	DISC-1	JB-P-9	GAS HOSE REEL
P-141	3/4	2#12, 1#12GND	++	DISC-2	JB-P-9	DIESEL HOSE REEL
P-142	3/4	2#12, 1#12GND	++	JB-P-9	JB-P-10	
P-143	3/4	2#12, 1#12GND	++	JB-P-10	PANEL A	+ +
P-144	3/4	2#12, 1#12GND	++	M-1/M-2	PANEL A	HOSE REEL MOTORS

CON	IDUIT	CONDUC	TORS		FROM	TO	F	REMARKS
NO.	SIZE	GENERAL		SPARES*				
G-100	1 1/2	2#2, 1#2GND			AVEC XFMR	METER		
G-101	1 1/2	2#2, 1#2GND			METER	MAIN DISCONNECT		
G-102	1 1/2	2#2, 1#2GND			MAIN DISCONNECT	PANEL A		
G-103	3/4	2#12, 1#12GND			CONNEX HEATER	PANEL A		
G-104	3/4	2#12, 1#12GND			RECEPTACLE 1	RECEPTACLE 2		
G-105	3/4	2#12, 1#12GND			RECEPTACLE 2	RECEPTACLE 3		
G-106	3/4	2#12, 1#12GND			RECEPTACLE 3	RECEPTACLE 3		
G-107	3/4	2#12, 1#12GND			RECEPTACLE 3	PANEL A		

COV	IDUIT	CONDUC	TORS	FROM	ТО	REMARKS
NO.	SIZE	CONTROL	SPARES*			
C-100	3/4	3#14, 1#14GND		LS-4	JB-C-1	FLOATS FOR TANK 4
C-101	3/4	3#14, 1#14GND		LS-3	JB-C-1	FLOATS FOR TANK 3
C-102	3/4	6#14, 1#14GND		JB-C-1	JB-C-2	
C-103	3/4	3#14, 1#14GND		LS-2	JB-C-2	FLOATS FOR TANK 2
C-104	3/4	9#14, 1#14GND		JB-C-2	JB-C-3	
C-105	3/4	3#14, 1#14GND		LS-1	JB-C-3	FLOATS FOR TANK 1
C-106	3/4	12#14, 1#14GND		JB-C-3	CP-1	
C-107	3/4	3#14, 1#14GND		LS-8	JB-C-4	FLOATS FOR TANK 8
C-108	3/4	3#14, 1#14GND		LS-7	JB-C-4	FLOATS FOR TANK 7
C-109	3/4	6#14, 1#14GND		JB-C-4	JB-C-5	
C-110	3/4	3#14, 1#14GND		LS-6	JB-C-5	FLOATS FOR TANK 6
C-111	3/4	9#14, 1#14GND		JB-C-5	JB-C-6	
C-112	3/4	3#14, 1#14GND		LS-5	JB-C-6	FLOATS FOR TANK 5
C-113	3/4	12#14, 1#14GND		JB-C-6	CP-1	
C-114	3/4	4#14, 1#14GND		LS-9A	JB-C-7	FLOATS FOR TANK 9A
C-115	3/4	4#14, 1#14GND		LS-9B	JB-C-7	FLOATS FOR TANK 9B
C-116	3/4	8#14, 1#14GND		JB-C-7	JB-C-8	
C-117	3/4	8#14, 1#14GND		JB-C-8	CP-1	
C-118	3/4	6#14, 1#14GND		MV-4	JB-C-9	
C-119	3/4	6#14, 1#14GND		MV-2	JB-C-9	
C-120	3/4	12#14, 1#14GND		JB-C-9	JB-C-10	
C-121	3/4	6#14, 1#14GND		MV-1	JB-C-10	
C-122	1	18#14, 1#14GND		JB-C-10	JB-C-11	
C-123	3/4	6#14, 1#14GND		MV-3	JB-C-11	
C-124	1 1/4	24#14, 1#14GND		JB-C-11	JB-C-12	
C-125	1 1/4	24#14, 1#14GND		JB-C-12	CP-1	
C-126	3/4	6#14, 1#14GND		MS-P9B	CP WIREWAY	
C-127	3/4	6#14, 1#14GND		MS-P9A	CP WIREWAY	
C-128	3/4	6#14, 1#14GND		MS-P8	CP WIREWAY	
C-129	3/4	6#14, 1#14GND		MS-P7	CP WIREWAY	
C-130	3/4	6#14, 1#14GND		MS-P6	CP WIREWAY	
C-131	3/4	6#14, 1#14GND		MS-P5	CP WIREWAY	
C-132	3/4	6#14, 1#14GND		MS-P4	CP WIREWAY	
C-133	3/4	6#14, 1#14GND		MS-P3	CP WIREWAY	
C-134	3/4	6#14, 1#14GND		MS-P2	CP WIREWAY	
C-135	3/4	6#14, 1#14GND		MS-P1	CP WIREWAY	
C-136	1	24#14, 1#14GND		CP WIREWAY	CP-1	MS-P8,7,6,5
C-137	1	24#14, 1#14GND		CP WIREWAY	CP-1	MS-P4,3,2,1
C-138	3/4	12#14, 1#14GND		CP WIREWAY	CP-1	MS-P9A,9B
C-139	3/4	1#12, 1#12GND		ESD-C01	CP-1	CONNEX ESD
C-140	3/4	1#12, 1#12GND		ESD-D01	CP-1	DISPENSER ESD
C-141	3/4	1#12, 1#12GND		ESD-T01	CP-1	TANK FARM ESD
C-142	3/4	1#12, 1#12GND		ESD-CW01	CP-1	CATWALK ESD

C	TIUDNC	CONDU	JCTORS	FROM	TO	REMARKS
NO.	SIZE	LIGHTING	SPARES*			
L-100	3/4	2#12, 1#12GND		POLE 1	POLE 2	
L-101	3/4	2#12, 1#12GND		POLE 2	POLE 3	
L-102	3/4	2#12, 1#12GND		POLE 3	SW-1	
L-103	3/4	2#12, 1#12GND		SW-1	PANEL A	
L-104	3/4	2#12, 1#12GND		POLE 4	POLE 5	
L-105	3/4	2#12, 1#12GND		POLE 5	POLE 6	
L-106	3/4	2#12, 1#12GND		POLE 6	JB-L-1	
L-107	3/4	2#12, 1#12GND		POLE 7	POLE 8	
L-108	3/4	2#12, 1#12GND		POLE 8	POLE 9	
L-109	3/4	2#12, 1#12GND		POLE 9	JB-L-1	
L-110	3/4	2#12, 1#12GND		POLE 10	POLE 11	
L-111	3/4	2#12, 1#12GND		POLE 11	JB-L-1	
L-112	3/4	2#12, 1#12GND		JB-L-1	SW-2	
L-113	3/4	2#12, 1#12GND		SW-2	PANEL A	
L-114	3/4	2#12, 1#12GND		L-1	SW-3	CONNEXES EXT. LIGHT
L-115	3/4	2#12, 1#12GND		SW-3	PANEL A	
L-116	3/4	2#12, 1#12GND		L-2	L-3	SALES CONNEX LTS
L-117	3/4	2#12, 1#12GND		L-3	SW-4	SALES CONNEX LTS
L-118	3/4	2#12, 1#12GND		SW-4	PANEL A	
L-119	3/4	2#12, 1#12GND		L-4	L5	SPILL RESP. CONNEX LTS
L-120	3/4	2#12, 1#12GND		L-5	SW-5	SPILL RESP. CONNEX LTS
L-121	3/4	2#12, 1#12GND		SW-5	PANEL A	
L-122	3/4	2#12, 1#12GND		L-6	JB-L-2	GAS KIOSK LIGHT
L-123	3/4	2#12, 1#12GND		L-7	JB-L-2	DIESEL KIOSK LIGHT
L-124	3/4	2#12, 1#12GND		JB-L-2	JB-L-3	
L-125	3/4	2#12, 1#12GND		JB-L-3	SW-5	
L-126	3/4	2#12, 1#12GND		SW-6	PANEL A	









BULK FUEL UPGRADES
CONDUIT SCHEDULE

NUNAPITCHUK, ALASKA



Sheet No.

# **NOTES**

- $\langle 1 \rangle$  3/4"X10' COPPER CLAD GROUND ROD.
- (2) #2 bcu ground ring buried min 30" below GRADE.
- $\langle \overline{3} \rangle$  #4 bCU GROUND TO TANKS.
- $\overline{\langle 4 \rangle}$  #6 bCU JUMPER TO FENCE.
- (5) BELOW GRADE BOND: EXOTHERMIC WELDMENT
  ABOVE GRADE BOND: FENCEPOST/STAIRS, SPLIT BOLT
  ABOVE GRADE BOND: DISPENSER/PANELS, SPLIT BOLT
  TANK SKID: EXOTHERMIC WELDMENT, DO NOT WELD
  TO TANK, TOUCH UP AND PAINT/GALVANIZE

AREA AFFECTED WHEN WELD IS COMPLETE.
PIPELINE: APPROVED PIPE GROUNDING CLAMP

- (6) #6 BRAID TO GATE AND MANDOORS.
- (7) EXTEND #6 GROUND TO BARBED WIRE AND BOND AT ALL CORNERS AND WHERE SHOWN.
- $\langle \overline{8} \rangle$  PROVIDE GROUND BAR FOR GROUND TESTING.
- (9) #4 bCU GROUND TO GROUND REEL.

[XXX] SEE SHEET E4 FOR CONDUIT SCHEDULE

SEE SPECIFICATION FOR CONDUIT ROUTING REQUIREMENTS.

HAZARDOUS BOUNDARIES SHOWN ON E8. PROVIDE SEAL OFF FITTINGS PER CODE. ACK FORD SALES





ELECTRICAL SITE PLAN, GROUNDING, LIGHTING PLAN NUNAPITCHUK. ALASKA

BULK FUEL UPGRADES

DATE	AH 7/28/21			
В	ΑH			
REVISION	1 ISSUED FOR BIDDING			
Ö.	-			

Plot 7/28/21
Designed WM
Drawn DJ
Approved WM

Sheet No.

E5

JOHNSON RIV

# NOTES

- (1) SEE SHEET E6 FOR CONDUIT DEVELOPMENT PLAN
- $\overline{\langle 2 \rangle}$  CHROMOLOX AIR HEATER-HCH-501M 332435
- (3) PLATE MOUNTED, ABOVE CONNEX DOORS

[XXX] SEE SHEET E4 FOR CONDUIT SCHEDULE.

SEE SPECIFICATION FOR CONDUIT ROUTING REQUIREMENTS.

HAZARDOUS BOUNDARIES SHOW ON E8. PROVIDE SEAL OFF FITTINGS PER CODE.

ALASKA ENERGY AUTH





BULK FUEL UPGRADES

& CONTROLS PLAN (1 OF 2)

BULK FUEI
B/21
POWER & CONTR

	NO.	REVISION	ВУ	DATE
_	1		ЧΗ	AH   7/28/
××××××××××××××××××××××××××××××××××××××				
-				
M				


SPILL RESPONSE/SALES CONNEX ELECTRICAL DETAIL

BOARDWALK END ELECTRICAL PLAN

2

- MAIN DISCONNECT [G-103] PANEL A [G-101] [G-102] [P-100] [G-106] Φ  $\sqrt{\mathsf{sw}}$ [G-107] ESD C01 (L) [C-139] [L-117] sw\ sw\

heet No.










BULK FUEL UPGRADES
POWER & CONTROLS PLAN (2 OF

5


NO. REVISION BY DATE
1 ISSUED FOR BIDDING AH 7/28/21

Plot 7/28/21
Designed WM
Drawn DJ
Approved WM

Sheet No.



(1) CLASS 1, DIVISION 1 RATING EXTENDS 5' IN ALL DIRECTIONS AROUND GASOLINE TANK VENTS.



 $\overline{3}$  THE AREA 18" ABOVE GRADE WITHIN 20' OF DUAL DISPENSER IS CLASS 1, DIVISION 2 RATED.

(4) THE AREA INSIDE THE DUAL PRODUCT DISPENSER AND INSIDE AND BELOW THE PAN BASIN IS CLASS 1, DIVISION 1 RATED.

 $\langle \overline{5} \rangle$  The area within 18" of the dual product dispenser is class 1, division 2 rated.

 $\overleftarrow{\text{6}}$  THE AREA WITHIN THE ENCLOSURE IS CLASS 1, DIVISION 1 RATED.

# CLASSIFICATION LEGEND


CLASS 1, DIVISION 1







BULK FUEL UPGRADES CLASSIFICATION PLAN

A H B≺








SCALE: NTS




GROUND ROD CONNECTION
SCALE: NTS







6 FENCE CONDUIT ROUTING DETAIL
SCALE: NTS



7 GATE CONDUIT ROUTING DETAIL
SCALE: NTS







BULK FUEL UPGRADES
GROUNDING AND ELECTRICAL DETAILS
NUNAPITCHUK, ALASKA

DATE	AH 7/28/21			
B	ΑH			
REVISION	ISSUED FOR BIDDING			
O	1			

Plot 7/28/21
Designed WM
Drawn DJ
Approved WM


Sheet No.


E9

J: \JobsData\30418.00 Aea — Nunapitchuk Bfu\00 Cadd 2019\01 Working Set\03 Electrical\30418 Details.dwg

,

STORAGE TANK LEVEL STATUS





DISPENSER PUMPS













ALARM AND PUMP CONTROL NARRATIVE

The control panel monitors and activates the tank level alarms, and powers the submersible pumps in each tank. The panel also provides for acknowledgement of alarm conditions, monitors emergency shutdown switch status and powers site lighting.

### ALARMS

Each fuel tank is equipped with a CRITICAL HIGH (LSHH - XX) Level Float switch that, when fuel reaches its level, opens a circuit (fails safe) and causes an alarm horn/strobe to signal a CRITICAL HIGH Level has been reached. The CRITICAL HIGH Level condition is indicated on the front of the panel as well, identifying the tank(s) with high level(s).

The operator can acknowledge the alarm by pressing the ALARM ACKNOWLEDGE button on the control panel. This extinguishes the strobe and silences the horn, but the front panel light will remain illuminated until sufficient fuel is drained from the tank to drop its fuel level below the CRITICAL HIGH float's sensing point. At that time the front panel light will extinguish."

The control logic for alarm is set up so that each new alarm condition will cause the audible and visual alarms to annunciate, regardless of any existing (acknowledged) alarm conditions.

The tanks are equipped with Low Level Floats (LSL). If tank fuel level drops below the float sensing level, the associated pump will stop until a transfer is completed to refill the tank to a level above the LSL. A pilot light on the front panel indicating TANK LOW will be illuminated

### EMERGENCY SHUTDOWN

The Emergency shutdown system, when engaged, will cause the alarm horn/strobe to be energized. There are two emergency shutdown stations; both by the front gates, north and south. The alarm is enabled by pushing the ESD button and is extinguished by pulling the Emergency Shutdown Switch (ESD) "out", clearing the signal. When an ESD button is pushed, all powered conductors to the dispensers are disconnected and all pumps are shut down. Lighting and alarms are NOT de-energized and will remain active.

### FUEL TRANSFER

The above ground storage tanks are filled by barge via the barge fuel pumping system. See Sheet C2 for a visual schematic and written description of the system.

DISPENSING & TRANSFER PUMPS

The hose reel STOP START remote operates the dispensing pump located in the dispensing tank.

When the dispensing pump is running a timer is activated and when the preset time has elapsed the pump is shut down. Should the timer shut the pump down before the required amount of fuel is provided. pushing the START button would cause the timer to reset allowing the pump to resume operation.

### Manual operation

By placing (and holding) the HOA switch in the HAND position, the fuel pump will start and run. Its RUN light will turn on and the pump will continue running until the low float is exposed, the pump experiences an overload condition where either the panel mounted motor starter control is opened internally, or an internal temperature sensor in the motor detects an overheat condition, or the operator releases the HOA switch. If a panel-based overload causes the shutdown, a pilot light on the panel front will be energized (no other indication will be given, other than the pump stopping). A RESET pushbutton on the pump motor starter located inside the panel must be pressed to clear the overload relay in order to allow the pump to restart. The HOA switch is spring loaded so that upon release it will return to OFF from the HAND position. The HAND or manual mode is provided for maintenance and testing however it could be used to operate the Dispensing system in the event of control failure.







UPGRADES LAYOUT FUEL PANEL BULK

A F

FUEL CONTROL PANEL CP-1 LAYOUT

**HOSE REEL CONTROL LAYOUT (TYP)** 

TRANSFER

NOT TO SCALE

|--|

 $\langle 1 \rangle$ 

|61|62|63|64|65|66|67|68|69|k2a|k2b|72a|12b|k3a|k2b|72a|k4b|72a|k4b|72a|k4b|72a|k4b|72a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|73a|k4b|

**CP-1 WIRE LIST** 

PILOT LIGH. SEE SPECIFICATION 26 09 20, 2.3 F 2 120V RELAY, 3PDT, SQUARE BASE SUITABLE FOR MODULE OPTIONS, SEE SPECIFICATION 26 09 20, 2.3 H 3 PILOT LIGHT, PUSH TO TEST. SEE SPECIFICATION 26 09 20, F 4 DIN RAIL MOUNTED POWER CONDITIONER. HARDWIRED SOLA CVW SERIES, 1kVA, 120V, ±1% REGULATION. P/N 22-23-210-8. (5) 3-POSITION SELECTOR SWITCH, SEE SPECIFICATION 26 09 20, 2.3 F 6 2-POLE, SINGLE PHASE, COMBINATION MOTOR CONTROLLER. EATON CAT. NUMBER EC-X-77-D-8-B-J-B-K, XT COMPACT COMBINATION MOTOR STARTER. MULTI-POLE CONTACTOR, 120V COIL, 10A RATED CONTACTS. # OF CONTACTS AS REQUIRED.

8 ALARM STROBE, 120V, FEDERAL ELECTRA FLASH #141 W/ RED LEXAN DOME. 9 INTEGRAL POWER DISTRIBUTION. NORMALLY OPEN PUSHBUTTON, SEE SPECIFICATION 26 09 20, 2.3 F |(11)| NORMALLY CLOSED PUSHBUTTON, SEE SPECIFICATION 26 09 20, 2.3 F 2-POSITION SELECTOR SWITCH, SEE SPECIFICATION 26 09 20, 2.3 F

COMPONENT SCHEDULE

ITFM

(13) HOFFMAN A364212WFSSLP OR APPROVED EQUAL. MULTI-POLE CONTACTOR, 120V COIL, 20A RATED CONTACTS. # OF CONTACTS AS REQUIRED.

15 NEMA 12 RATED ENCLOSURE WITH LOCKABLE FRONT DOOR. HOFFMAN OR EQUAL. SIZE AS REQUIRED.

ADJUSTABLE TIME DELAY RELAY, MODULE FOR ITEM 2 ABOVE, ALLEN BRADLEY 700-AT3A1.

ADJUSTABLE TIME DELAY RELAY, MODULE FOR ITEM 3 ABOVE, ALLEN BRADLEY 700-AT3A1.

SEE E1 FOR FIELD MOUNTED ELECTRICAL EQUIPMENT SCHEDULE.










UPGRADES COMPONENT FUEL AND BULK LIST

DATE	AH 7/28/21				
λЯ	ΑH				
REVISION	ISSUED FOR BIDDING				
ОN	-				
		T		T	_







Plot Date: 7/28/2021 3:13 PM

Bfu\00 Cadd 2019\01 Working Set\03 Electrical\30418.00 Ladder Diagram.dwg








TRANSFER PUMPS P-1 AND P-2 LADDER DIAGRAMS BULK FUEL UPGRADES NUNAPITCHUK, ALASKA


BY DATE AH 7/28/21

REVISION ISSUED FOR BIDDING

Plot Date 7/28/21

Sheet No. E14











GASOLINE DISPENSER PUMP LADDER DIAGRAM







ALASKA ENERGY AUTHORITY





BULK FUEL UPGRADES
TRANSFER PUMPS P-5 AND P-6
LADDER DIAGRAMS
NUNAPITCHUK, ALASKA

ISSUED FOR BIDDING AH 7/28/21

Designed WM DJ Prown DJ Approved WM

Sheet No.

